

What Are Custom Hex Bolt (GHJ Series) Used For?

Engineering Hardware & Fasteners · engineeringhardware.com/applications/cad-svg-009-genericpart

[Fasteners/General Components Custom Hex Bolt \(GHJ Series\) — GB/T 5783 / ISO 4017 \(Series 009\)](#)/Applications

[General Components · GB/T 5783 / ISO 4017 · Application Guide](#)

Typical applications, the industries that specify custom hex bolt (ghj series), and how to choose the right size, material and finish for the joint.

Custom Hex Bolt (GHJ Series) are used for a specific function defined by the part drawing rather than by a catalog fastener standard. They are manufactured to GB/T 5783 / ISO 4017, and selection is driven by the nominal size, the fit and tolerance the assembly requires, and the service environment.

Primary duty

A specific function defined by the part drawing rather than by a catalog fastener standard

Governing standard

GB/T 5783 / ISO 4017

Nominal size range

1 mm to 8 mm

Category

General Components

Application notes are general engineering guidance. Verify the property class and any approval requirement against your own design calculation.



Custom Hex Bolt (GHJ Series) are selected when an assembly calls for a specific function defined by the part drawing rather than by a catalog fastener standard. This application guide to the GB/T 5783 / ISO 4017 type covers concrete end-uses, the specification checklist, correct installation, and where an alternative fastener performs better. Stocked across roughly 1 mm to 8 mm, they cover general to heavy-duty work.

Typical Applications for Custom Hex Bolt (GHJ Series) — GB/T 5783 / ISO 4017 (Series 009)

The most common settings where these are specified:

- **General machine building:** fastening covers, brackets, motors and sub-assemblies on production equipment.
- **Maintenance & repair (MRO):** a stocked size for servicing existing plant where the original fastener spec must be matched.
- **Fabrication & metalwork:** bench and on-site assembly of steel frames, enclosures and weldments.

How to Specify Custom Hex Bolt (GHJ Series) — GB/T 5783 / ISO 4017 (Series 009) for Your Application

- **Size:** Select on nominal size, and confirm it against the mating feature in the assembly. This product spans 1 mm–8 mm; check the full table below for the exact dimensions of each size.
- **Material:** Choose the material and finish for the service environment — plated steel for general use, stainless for corrosion resistance.
- **Environment:** For damp, coastal or chemical exposure prefer A4/316 stainless or a suitable coating; indoors, plated steel or A2 is usually sufficient.
- **Standard:** This product is supplied to GB/T 5783 / ISO 4017. Quoting the standard on your order guarantees interchangeable dimensions between suppliers.

Where Custom Hex Bolt (GHJ Series) — GB/T 5783 / ISO 4017 (Series 009) Are Not the Right Choice

Match the fastener to the load, environment and whether the joint must be reopened; the wrong class or style is the usual cause of joint failure.

Technical Drawing

Customize the parameters below — every spec field is editable, and the drawing redraws to match the values you choose. Changing the size will snap the other fields to that size's standard values; you can then override any individual value.

Sends the selected values to the quote form below.

Request a Quote

The form below follows the current technical drawing configuration. Change the drawing values above and the request details update automatically.

Dimensions & Specifications (GB/T 5783 / ISO 4017)

Size designation	Outer diameter / width (mm)	Length / height (mm)	Bore / thread (mm)	Material	Reference standard
Size 1	10	20	6	C45 carbon steel	GB/T 1804-m
Size 2	12	25	8	C45 carbon steel	GB/T 1804-m
Size 3	16	32	10	C45 carbon steel	GB/T 1804-m
Size 4	20	40	12	C45 carbon steel	GB/T 1804-m
Size 5	25	50	16	C45 carbon steel	GB/T 1804-m
Size 6	32	63	20	C45 carbon steel	GB/T 1804-m
Size 7	40	80	25	C45 carbon steel	GB/T 1804-m
Size 8	50	100	30	C45 carbon steel	GB/T 1804-m

Inside the plant

Manufactured in our own plant

This part is cold-formed, threaded, heat-treated and finished in-house. The stages below are where its class and finish are actually decided.

1.



01

Cold heading

Wire rod is drawn to size and cold-formed into blanks. Forming rather than cutting keeps the grain flow continuous around the head, which is where a bolt is most likely to fail.

Head dimensions and under-head radius checked at set-up and per shift.



2.

02

Thread rolling

Threads are rolled between hardened dies rather than cut. Rolled threads are stronger in fatigue than cut threads and hold pitch and flank angle far more consistently across a batch.

Go / no-go ring gauges to ISO 965 tolerance class 6g.

3.



03

Heat treatment

Quench-and-temper brings carbon and alloy steel to the property class ordered — 8.8, 10.9 or 12.9 — with the furnace charge tracked so a finished lot can be traced back to it.

Core hardness and tensile tested per lot to ISO 898-1.

4.



04

Surface treatment

Zinc, zinc-nickel, hot-dip galvanizing, black oxide, phosphate and Dacromet, selected against the service environment rather than against the price list.

Coating thickness and neutral salt spray hours to ISO 9227.

Frequently Asked Questions

What are Custom Hex Bolt (GHJ Series) — GB/T 5783 / ISO 4017 (Series 009) used for?

A specific function defined by the part drawing rather than by a catalog fastener standard. They are supplied to GB/T 5783 / ISO 4017.

Which industries use Custom Hex Bolt (GHJ Series) — GB/T 5783 / ISO 4017 (Series 009)?

They are commonly specified in general machine building, maintenance & repair (mro) and fabrication & metalwork, among other sectors.

How do I choose the right size of Custom Hex Bolt (GHJ Series) — GB/T 5783 / ISO 4017 (Series 009)?

Select on nominal size and on the fit the assembly requires. This product is available from 1 mm to 8 mm; the full dimension table on this page lists each size.

Are Custom Hex Bolt (GHJ Series) — GB/T 5783 / ISO 4017 (Series 009) made to a recognized standard?

Yes — they are manufactured to GB/T 5783 / ISO 4017, so dimensions are interchangeable between suppliers when you quote the standard on your order.

Can I get a quote for Custom Hex Bolt (GHJ Series) — GB/T 5783 / ISO 4017 (Series 009) in the size and material I need?

Yes. Use the technical drawing and quote form on this page to set the size and options, then send the exact configuration to our team for pricing and lead time.

Related Pages

Product page: [Custom Hex Bolt \(GHJ Series\) — GB/T 5783 / ISO 4017 \(Series 009\) — specifications & sizes](#)

Custom Hex Bolt (GHJ Series) — GB/T 5783 / ISO 4017 (Series 009) Specification Guides

- [A4 stainless Custom Hex Bolt \(GHJ Series\) — GB/T 5783 / ISO 4017 \(Series 009\)](#)

Related Fastener Applications

- [CDZZ Limit Post — GB/T 6170 / ISO 4032 \(Series 062\) applications](#)
- [Custom Machined Component — GB/T 5782 / ISO 4014 \(Series 004\) applications](#)
- [Custom Machined Component — ISO / DIN \(Series 115\) applications](#)
- [Custom Machined Component — ISO / DIN \(Series 130\) applications](#)
- [Cylinder Connecting Sleeve — GB/T 5783 / ISO 4017 \(Series 013\) applications](#)
- [Engineered Component — GB/T 78 / ISO 4027 \(Series 025\) applications](#)