

Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040) — GB/T 67 / ISO 1580

Engineering Hardware · engineeringhardware.com/fastener/cad-svg-040-panhead

[Fasteners/ Screws/](#) Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040)

Screws · CAD Pan Head Screws

Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040) to GB/T 67 / ISO 1580. Full dimensional table, materials, finishes and quotation. 6 sizes listed.



Technical Drawing

Customize the parameters below — every spec field is editable, and the drawing redraws to match the values you choose. Changing the size will snap the other fields to that size's standard values; you can then override any individual value.

Sends the selected values to the quote form below.

Request a Quotation for Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040)

Tell us the size, material, finish and quantity you need for Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040) (GB/T 67 / ISO 1580) and our team will respond within one business day. Click "Request this configuration" on the drawing above to send the parameters you just chose straight into this form.

Category Type Standard Thread size Material Finish

Dimensions & Specifications (GB/T 67 / ISO 1580)

Every row below is a starting point for the customizer above — pick any size and the drawing will redraw to that row.

Size	Pitch (mm)	Length L (mm)	Head diameter dk (mm)	Head height k (mm)	Cross recess	Reference standard
M3	0.5	20	5.6	1.8	PH1	ISO 7045 / GB/T 818
M4	0.7	25	8.0	2.4	PH2	ISO 7045 / GB/T 818
M5	0.8	30	9.5	3.0	PH2	ISO 7045 / GB/T 818
M6	1.0	40	12.0	3.6	PH3	ISO 7045 / GB/T 818
M8	1.25	50	16.0	4.8	PH3	ISO 7045 / GB/T 818
M10	1.5	60	20.0	6.0	PH4	ISO 7045 / GB/T 818

Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040) (GB/T 67 / ISO 1580) are a type of screws used across industrial assembly. Below is the complete size table together with material, standard and application guidance.

What Are Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040)?

Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040) are screws defined by GB/T 67 / ISO 1580. They are selected by thread size and the dimensional characteristics shown below, and are available in a range of materials and finishes to suit the application and environment.

CAD Source Reference

This page is generated from an original native CAD part model (SolidWorks .SLDPRT) of the slotted pan head screw — gb/t 67 / iso 1580 (series 040) family maintained by our engineering team, covering 11 recorded size configurations. The technical drawing shown above is rebuilt parametrically from the dimensional table, so it always reflects the exact size and configuration you select. Native CAD files (STEP / SLPRT) can be supplied with your quotation on request.

Materials & Finishes

Common materials include carbon steel (typically zinc plated or hot-dip galvanized), alloy steel in property classes 8.8, 10.9 and 12.9, and stainless steel A2 (304) or A4 (316) for corrosion resistance. Specify the material, property class and surface finish appropriate to your load and environment.

Typical Applications

Machine assembly, tooling, enclosures and precision equipment where a clean, controllable drive and head form are needed. [Read the full application guide for Slotted Pan Head Screw — GB/T 67 / ISO 1580 \(Series 040\) →](#)

Related Fasteners

- [Phillips Pan Head Machine Screw — GB/T 818 / ISO 7045 \(Series 033\) — GB/T 818 / ISO 7045](#)
- [Phillips Pan Head Self-Tapping Screw — GB/T 845 / ISO 7049 \(Series 032\) — GB/T 845 / ISO 7049](#)
- [Phillips Pan Head Machine Screw — GB/T 818 / ISO 7045 \(Series 035\) — GB/T 818 / ISO 7045](#)
- [Phillips Pan Head Machine Screw — GB/T 818 / ISO 7045 \(Series 034\) — GB/T 818 / ISO 7045](#)
- [Sheet-Metal Self-Tapping Screw — GB/T 845 / ISO 7049 \(Series 045\) — GB/T 845 / ISO 7049](#)

Pricing

Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040) are stocked and supplied to order. Pricing starts from approximately US\$0.050 per piece for standard sizes in carbon steel; final pricing depends on size, material, finish and order quantity (MOQ applies). Submit your exact configuration with the quote form above.

Frequently Asked Questions

What standard and drive type do Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040) use?

Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040) are manufactured to GB/T 67 / ISO 1580 and use a cross recess (Phillips/Pozi) drive. The dimensional values on this page follow that standard.

What sizes are available for Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040)?

The table on this page lists 6 sizes for Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040), ranging from M3 to M10. Sizes outside the table can be quoted on request.

In which materials are Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040) supplied?

Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040) are supplied in alloy steel (typically 10.9 / 12.9 for socket screws), carbon steel and stainless A2 / A4, with finishes including zinc plating, hot-dip galvanizing and black oxide. Choose material and finish to suit the load and the service environment for Slotted Pan Head Screw — GB/T 67 / ISO 1580 (Series 040).

How do I request a quotation?

Use the parametric drawing on this page to set the exact configuration (size, material, finish) and click "Request this configuration" — a specialist from engineeringhardware.com will respond within one business day.

More Screws

← Previous [Hex Socket Cone Point Set Screw — GB/T 77 / ISO 4026 \(Series 022\)](#) [GB/T 77 / ISO 4026](#) Next → [Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 \(Series 023\)](#) [GB/T 2673 / ISO 14583](#)