

# Stud — GB/T 15389 / DIN 939 (Series 096) — GB/T 15389 / DIN 939

Engineering Hardware · [engineeringhardware.com/fastener/cad-svg-096-stud](https://engineeringhardware.com/fastener/cad-svg-096-stud)

[Fasteners/ Bolts/ Stud](#) — GB/T 15389 / DIN 939 (Series 096)

Bolts · CAD Studs & Threaded Rods

Stud — GB/T 15389 / DIN 939 (Series 096) to GB/T 15389 / DIN 939. Full dimensional table, materials, finishes and quotation. 10 sizes listed.



## Technical Drawing

Customize the parameters below — every spec field is editable, and the drawing redraws to match the values you choose.

Changing the size will snap the other fields to that size's standard values; you can then override any individual value.

Sends the selected values to the quote form below.

## Request a Quotation for Stud — GB/T 15389 / DIN 939 (Series 096)

Tell us the size, material, finish and quantity you need for Stud — GB/T 15389 / DIN 939 (Series 096) (GB/T 15389 / DIN 939) and our team will respond within one business day. Click "Request this configuration" on the drawing above to send the parameters you just chose straight into this form.

Category Type Standard Thread size Material Finish

## Dimensions & Specifications (GB/T 15389 / DIN 939)

Every row below is a starting point for the customizer above — pick any size and the drawing will redraw to that row.

| Thread size | Pitch (mm) | Length L (mm) | Engagement depth bm (mm) | Material            | Reference standard |
|-------------|------------|---------------|--------------------------|---------------------|--------------------|
| M6          | 1.0        | 50            | 8                        | Cl. 8.8 alloy steel | DIN 939 / GB/T 901 |
| M8          | 1.25       | 60            | 10                       | Cl. 8.8 alloy steel | DIN 939 / GB/T 901 |
| M10         | 1.5        | 80            | 15                       | Cl. 8.8 alloy steel | DIN 939 / GB/T 901 |
| M12         | 1.75       | 100           | 18                       | Cl. 8.8 alloy steel | DIN 939 / GB/T 901 |
| M14         | 2.0        | 120           | 21                       | Cl. 8.8 alloy steel | DIN 939 / GB/T 901 |
| M16         | 2.0        | 150           | 24                       | Cl. 8.8 alloy steel | DIN 939 / GB/T 901 |
| M20         | 2.5        | 180           | 30                       | Cl. 8.8 alloy steel | DIN 939 / GB/T 901 |
| M24         | 3.0        | 200           | 36                       | Cl. 8.8 alloy steel | DIN 939 / GB/T 901 |
| M30         | 3.5        | 240           | 45                       | Cl. 8.8 alloy steel | DIN 939 / GB/T 901 |
| M36         | 4.0        | 280           | 54                       | Cl. 8.8 alloy steel | DIN 939 / GB/T 901 |

Stud — GB/T 15389 / DIN 939 (Series 096) (GB/T 15389 / DIN 939) are a type of bolts used across industrial assembly. Below is the complete size table together with material, standard and application guidance.

## What Are Stud — GB/T 15389 / DIN 939 (Series 096)?

Stud — GB/T 15389 / DIN 939 (Series 096) are bolts defined by GB/T 15389 / DIN 939. They are selected by thread size and the dimensional characteristics shown below, and are available in a range of materials and finishes to suit the application and environment.

## CAD Source Reference

This page is generated from an original native CAD part model (SolidWorks .SLDPRT) of the stud — gb/t 15389 / din 939 (series 096) family maintained by our engineering team, covering 2 recorded size configurations. The technical drawing shown above is rebuilt parametrically from the dimensional table, so it always reflects the exact size and configuration you select. Native CAD files (STEP / SLDPRPT) can be supplied with your quotation on request.

## Materials & Finishes

Common materials include carbon steel (typically zinc plated or hot-dip galvanized), alloy steel in property classes 8.8, 10.9 and 12.9, and stainless steel A2 (304) or A4 (316) for corrosion resistance. Specify the material, property class and surface finish appropriate to your load and environment.

## Typical Applications

Structural steelwork, machinery, automotive and general assembly where high-strength, removable joints are required. [Read the full application guide for Stud — GB/T 15389 / DIN 939 \(Series 096\) →](#)

## Related Fasteners

- [Equal-End Stud Bolt — GB/T 901 / DIN 939 \(Series 093\) — GB/T 901 / DIN 939](#)
- [Stud Bolt, Double-End — GB/T 15389 / DIN 938 \(Series 092\) — GB/T 15389 / DIN 938](#)
- [Threaded Rod — ISO / DIN \(Series 153\) — ISO / DIN](#)
- [Stud Bolt, Double-End — GB/T 901 / DIN 939 \(Series 091\) — GB/T 901 / DIN 939](#)
- [Stud / Threaded Rod — ISO / DIN \(Series 154\) — ISO / DIN](#)

## Pricing

Stud — GB/T 15389 / DIN 939 (Series 096) are stocked and supplied to order. Pricing starts from approximately US\$0.080 per piece for standard sizes in carbon steel; final pricing depends on size, material, finish and order quantity (MOQ applies). Submit your exact configuration with the quote form above.

## Frequently Asked Questions

Which standard governs Stud — GB/T 15389 / DIN 939 (Series 096), and how are they driven?

Stud — GB/T 15389 / DIN 939 (Series 096) are manufactured to GB/T 15389 / DIN 939 and use the standard drive for this product family. The dimensional values on this page follow that standard.

What sizes are available for Stud — GB/T 15389 / DIN 939 (Series 096)?

The table on this page lists 10 sizes for Stud — GB/T 15389 / DIN 939 (Series 096), ranging from M6 to M36. Sizes outside the table can be quoted on request.

In which materials are Stud — GB/T 15389 / DIN 939 (Series 096) supplied?

Stud — GB/T 15389 / DIN 939 (Series 096) are supplied in carbon steel in property classes 8.8 / 10.9 / 12.9 and stainless A2 (304) / A4 (316), with finishes including zinc plating, hot-dip galvanizing and black oxide. Choose material and finish to suit the load and the service environment for Stud — GB/T 15389 / DIN 939 (Series 096).

How do I request a quotation?

Use the parametric drawing on this page to set the exact configuration (size, material, finish) and click "Request this configuration" — a specialist from engineeringhardware.com will respond within one business day.

More Bolts

[← Previous Threaded Rod — GB/T 15389 / DIN 939 \(Series 095\)GB/T 15389 / DIN 939](#)[Next → Hex Bolt, Fully Threaded — GB/T 5783 / ISO 4017 \(Series 011\)GB/T 5783 / ISO 4017](#)