

Hex Keys (Allen Keys) — ISO 2936

Engineering Hardware · engineeringhardware.com/fastener/hex-keys-allen-keys

[Fasteners/ Tools/](#) Hex Keys (Allen Keys)

Tools · Hex Keys (Allen Keys)

Hex Keys (Allen Keys) to ISO 2936. Full dimensional table, materials, finishes and quotation. 29 sizes listed.



Technical Drawing

Customize the parameters below — every spec field is editable, and the drawing redraws to match the values you choose.

Changing the size will snap the other fields to that size's standard values; you can then override any individual value.

Sends the selected values to the quote form below.

Request a Quotation for Hex Keys (Allen Keys)

Tell us the size, material, finish and quantity you need for Hex Keys (Allen Keys) (ISO 2936) and our team will respond within one business day. Click "Request this configuration" on the drawing above to send the parameters you just chose straight into this

form.

Category Type Standard Thread size Material Finish

Dimensions & Specifications (ISO 2936)

Every row below is a starting point for the customizer above — pick any size and the drawing will redraw to that row.

Wrench size s (mm)	Common bolt sizes	Short leg (mm)	Long leg (mm)	Reference standard
0.7	M1	28	51	ISO 2936 / DIN 911
0.9	M1.1	28	56	ISO 2936 / DIN 911
1.0	M1.2	32	56	ISO 2936 / DIN 911
1.3	M1.6	36	63	ISO 2936 / DIN 911
1.5	M2	40	71	ISO 2936 / DIN 911
2.0	M2.5	50	90	ISO 2936 / DIN 911
2.5	M3	56	100	ISO 2936 / DIN 911
3.0	M4	63	112	ISO 2936 / DIN 911
4.0	M5	71	125	ISO 2936 / DIN 911
5.0	M6	80	140	ISO 2936 / DIN 911
6.0	M8	90	160	ISO 2936 / DIN 911
7.0	---	100	180	ISO 2936 / DIN 911
8.0	M10	112	200	ISO 2936 / DIN 911
9.0	---	112	200	ISO 2936 / DIN 911
10.0	M12	125	224	ISO 2936 / DIN 911
12.0	M14	140	250	ISO 2936 / DIN 911
14.0	M16	160	280	ISO 2936 / DIN 911
17.0	M20	180	315	ISO 2936 / DIN 911
19.0	M22	200	355	ISO 2936 / DIN 911
22.0	M24	224	400	ISO 2936 / DIN 911
24.0	M27	250	450	ISO 2936 / DIN 911
27.0	M30	280	500	ISO 2936 / DIN 911
32.0	M36	315	560	ISO 2936 / DIN 911
36.0	M42	355	630	ISO 2936 / DIN 911
41.0	M48	400	710	ISO 2936 / DIN 911
46.0	---	450	800	ISO 2936 / DIN 911

Wrench size s (mm)	Common bolt sizes	Short leg (mm)	Long leg (mm)	Reference standard
50.0	---	500	900	ISO 2936 / DIN 911
55.0	---	500	900	ISO 2936 / DIN 911
60.0	---	560	1000	ISO 2936 / DIN 911

Hex Keys (Allen Keys) (ISO 2936) are a type of tools used across industrial assembly. Below is the complete size table together with material, standard and application guidance.

What Are Hex Keys (Allen Keys)?

Hex Keys (Allen Keys) are tools defined by ISO 2936. They are selected by thread size and the dimensional characteristics shown below, and are available in a range of materials and finishes to suit the application and environment.

Materials & Finishes

Common materials include carbon steel (typically zinc plated or hot-dip galvanized), alloy steel in property classes 8.8, 10.9 and 12.9, and stainless steel A2 (304) or A4 (316) for corrosion resistance. Specify the material, property class and surface finish appropriate to your load and environment.

Typical Applications

Driving and servicing socket fasteners during assembly and maintenance. [Read the full application guide for Hex Keys \(Allen Keys\)](#)

→

Pricing

Hex Keys (Allen Keys) are stocked and supplied to order. Pricing starts from approximately US\$0.10 per piece for standard sizes in carbon steel; final pricing depends on size, material, finish and order quantity (MOQ applies). Submit your exact configuration with the quote form above.

Frequently Asked Questions

Which standard governs Hex Keys (Allen Keys), and how are they driven?

Hex Keys (Allen Keys) are manufactured to ISO 2936 and use the standard drive for this product family. The dimensional values on this page follow that standard.

Which sizes of Hex Keys (Allen Keys) does engineeringhardware.com supply?

The table on this page lists 29 sizes for Hex Keys (Allen Keys), ranging from 0.7 to 60.0. Sizes outside the table can be quoted on request.

In which materials are Hex Keys (Allen Keys) supplied?

Hex Keys (Allen Keys) are supplied in chrome-vanadium steel, with finishes including zinc plating, hot-dip galvanizing and black oxide. Choose material and finish to suit the load and the service environment for Hex Keys (Allen Keys).

How do I request a quotation?

Use the parametric drawing on this page to set the exact configuration (size, material, finish) and click "Request this configuration" — a specialist from engineeringhardware.com will respond within one business day.