A4 (316) Stainless Steel Hex Nut

A4 Stainless Steel Hex Nut are supplied to ISO 3506 group A4 (316 / 1.4401), commonly supplied A4-80. Corrosion behaviour is superior, including marine and chloride environments, the material is largely non-magnetic, and the usable service range is approx. -200 °C to +400 °C, subject to the property class and the joint. In practice this grade is specified for marine, coastal and chemical applications.

Grade

ISO 3506 group A4 (316 / 1.4401), commonly supplied A4-80

Corrosion resistance

Superior, including marine and chloride environments

Magnetic response

Largely non-magnetic

Service temperature

approx. -200 °C to +400 °C, subject to the property class and the joint

Property values are typical for the grade. Certified mechanical test data is available on request for production orders.

For hex nut in A4 Stainless Steel, the controlling selection factors are corrosion exposure, strength requirement and service temperature. The grade data for A4 Stainless Steel (ISO 3506 group A4 (316 / 1.4401), commonly supplied A4-80) is summarized below together with every size supplied.

Why Choose A4 Stainless Steel for Hex Nut — GB/T 41 / ISO 4034 (Series 060)

Specified for marine, coastal and chemical applications. For hex nut — gb/t 41 / iso 4034 (series 060), this matters when superior, including marine and chloride environments is the primary requirement.

Mechanical & Physical Properties

Grade designation	ISO 3506 group A4 (316 / 1.4401), commonly supplied A4-80
Magnetic response	Largely non-magnetic
Service temperature	approx. -200 °C to +400 °C, subject to the property class and the joint
Corrosion characteristic	Superior, including marine and chloride environments

Corrosion Behavior in Service

A4 (316) adds 2–3% molybdenum to the A2 (304) composition, which dramatically improves resistance to chloride-pitting corrosion. For Hex Nut — GB/T 41 / ISO 4034 (Series 060) in marine, coastal, swimming-pool or food-processing environments, A4 is the default selection.

Galvanic & Galling Considerations

Two important notes for stainless hex nut — gb/t 41 / iso 4034 (series 060): (1) stainless can gall on stainless threads under load — use a thread lubricant or anti-galling compound, especially for M6 and below; (2) when joined to aluminum or galvanized steel, stainless can drive galvanic corrosion of the less-noble metal in wet service — isolate with a coating or sleeve where appropriate.

Using Stainless Fasteners in Aluminum

Expect the aluminum to corrode, not the fastener — stainless sits higher in the galvanic series, so the aluminum is the one that gives up material. A small fastener in a thick

section spreads the loss over a large area and is usually fine; a large fastener in thin sheet concentrates it and is not. Keep water out of the joint, or isolate the two metals with a nylon or coated washer and a sealant.

Sizes of Hex Nut — GB/T 41 / ISO 4034 (Series 060) Available in A4 Stainless Steel

Size	Pitch (mm)	Width across flats s (mm)	Width across corners e (mm)	Nut height
M3	0.5	5.5	6.01	2.4
M4	0.7	7.0	7.66	3.2
M5	0.8	8.0	8.79	4.7
M6	1.0	10.0	11.05	5.2
M8	1.25	13.0	14.38	6.8
M10	1.5	16.0	17.77	8.4
M12	1.75	18.0	20.03	10.8
M14	2.0	21.0	23.36	12.8
M16	2.0	24.0	26.75	14.8
M18	2.5	27.0	30.14	15.8
M20	2.5	30.0	33.53	18.0
M24	3.0	36.0	39.98	21.5
M30	3.5	46.0	50.85	25.6

Size	Pitch (mm)	Width across flats s (mm)	Width across corners e (mm)	Nut height
M36	4.0	55.0	60.79	31.0

Dimensions are independent of the material: every size above is available in A4 Stainless Steel.

Custom manufacturing · Made to drawing

Need this nut in a grade that is not listed?

A4 Stainless Steel is one of the grades the catalog describes. Locking method is specifiable independently of the rest: nylon insert, all-metal deformed thread, serrated flange, or none. Made by cold heading or tapping.

Minimum order from 2,000 pieces; samples within 7 days of drawing approval.

Custom nut manufacturing (https://engineeringhardware.com/custom/nuts/)

Send a drawing (https://engineeringhardware.com/custom/nuts/#rfq)

Technical Drawing

Customize the parameters below — every spec field is editable, and the drawing redraws to match the values you choose. Changing the size will snap the other fields to that size's standard values; you can

then override any individual value.

Dimensioned line drawing of M3 Hex Nut — GB/T 41 / ISO 4034 (Series 060) to GB/T 41 / ISO 4034. Side view and top view, drawn to the dimensions in the table below and redrawn for any size selected.

Opens a short step to confirm the exact specification before you enter contact details.

Request a Quote

Click “Request this configuration” under the drawing to confirm the exact specification, then add your contact details. You can also send the request without a specification — but only an accurate selection gets an accurate quote.

Dimensions & Specifications (GB/T 41 / ISO 4034)

Size	Pitch (mm)	Width across flats s (mm)	Width across corners e (mm)	Nut height
M3	0.5	5.5	6.01	2.4
M4	0.7	7.0	7.66	3.2
M5	0.8	8.0	8.79	4.7
M6	1.0	10.0	11.05	5.2
M8	1.25	13.0	14.38	6.8
M10	1.5	16.0	17.77	8.4
M12	1.75	18.0	20.03	10.8
M14	2.0	21.0	23.36	12.8
M16	2.0	24.0	26.75	14.8
M18	2.5	27.0	30.14	15.8
M20	2.5	30.0	33.53	18.0
M24	3.0	36.0	39.98	21.5
M30	3.5	46.0	50.85	25.6
M36	4.0	55.0	60.79	31.0

Materials & Grades

Select a material class to see the grades we supply it in. Each designation is listed with its ISO/EN, AISI/SAE, JIS and GB equivalents.

Stainless Steel

Carbon Steel 66

Alloy Steel 41

Bearing Steel 5

Spring Steel 25

Aluminum and Aluminum Alloys 21

Brass 17

Bronze 11

Copper 8

Titanium and Titanium Alloys 18

Nickel and Nickel Alloys 22

Iron-Nickel and High-Temperature Alloys 10

Tool Steel and Specialty Hardened Steel 9

Structural and Construction Steel 9

Stainless Steel

Austenitic Stainless Steel

A1
AISI 303 · SAE 303 · SUS303 · EN 1.4305 · X8CrNiS18-9

A2
AISI 304 · SAE 304 · SUS304 · EN 1.4301 · X5CrNi18-10 · 06Cr19Ni10

304L
AISI 304L · SUS304L · EN 1.4307 · X2CrNi18-9 · 022Cr19Ni10

302
AISI 302 · SUS302 · EN 1.4310

305
AISI 305 · SUS305 · EN 1.4303

A4
AISI 316 · SAE 316 · SUS316 · EN 1.4401 · X5CrNiMo17-12-2 · 06Cr17Ni12Mo2

316L
AISI 316L · SUS316L · EN 1.4404 · X2CrNiMo17-12-2 · 022Cr17Ni12Mo2

321
AISI 321 · SUS321 · EN 1.4541 · X6CrNiTi18-10

310 / 310S
AISI 310 · AISI 310S · SUS310S · EN 1.4845

302HQ
AISI 302HQ

A3

A5

347
AISI 347 · SUS347 · EN 1.4550 · X6CrNiNb18-10

309 / 309S
AISI 309 · AISI 309S · SUS309S

Martensitic Stainless Steel

AISI 410
SUS410 · EN 1.4006 · X12Cr13 · 12Cr13

AISI 420
SUS420J1 · SUS420J2 · EN 1.4021 · EN 1.4028 · 20Cr13 · 30Cr13

AISI 431
SUS431 · EN 1.4057 · X17CrNi16-2

C1

C3

C4

AISI 440A

AISI 440B

AISI 440C
SUS440C · EN 1.4125

Ferritic Stainless Steel

AISI 430
SUS430 · EN 1.4016 · X6Cr17 · 10Cr17

F1

AISI 434

AISI 444

Precipitation-Hardening Stainless Steel

17-4 PH
AISI 630 · UNS S17400 · SUS630 · EN 1.4542 · X5CrNiCuNb16-4

15-5 PH
UNS S15500

17-7 PH
UNS S17700

Duplex and Super Duplex Stainless Steel

Duplex 2205
UNS S31803 · UNS S32205 · EN 1.4462

Super Duplex 2507
UNS S32750 · EN 1.4410

D2

D4

D6

D8

Lean Duplex 2101
UNS S32101

Super Duplex S32760
UNS S32760 · EN 1.4501

Carbon Steel

Low-Carbon Steel

SAE 1006

SAE 1008

SAE 1010

SAE 1018

SAE 1020

Q195

Q235

SAE 1012

SAE 1015

Q215

ML08

ML08Al
ML10
ML15
ML20
SWRCH6A
SWRCH8A
SWRCH10A
SWRCH12A
SWRCH15A
SWRCH18A

Medium-Carbon Steel

SAE 1035
SAE 1045
S45C
C45
SAE 1030
SAE 1040
SAE 1050
30
35
40
45
50
S35C
S40C
S50C
C35

C40

High-Carbon Steel

SAE 1060
SAE 1070
65Mn
SAE 1065
SAE 1075
SAE 1080
SAE 1085
SAE 1090
SAE 1095
60
65
70
75
80
85

Cold-Heading Steel

SWRCH22A
10B21
SWRCH22K
SWRCH25K
SWRCH30K
SWRCH35K
SWRCH40K

ML20Mn
ML25
ML30
ML35
ML40
15B25

Alloy Steel

Chromium Steel

40Cr
45Cr
AISI 5140
SAE 5140
AISI 5120
SAE 5120
SCr420
SCr440

Chromium-Molybdenum Steel

35CrMo
42CrMo
AISI 4140
SCM435
SCM440
42CrMo4
30CrMo

AISI 4130
SAE 4130
SAE 4140
AISI 4142
AISI 4145
SCM415
SCM420
SCM445
EN 1.7220
EN 1.7225
25CrMo4
34CrMo4

Nickel-Chromium-Molybdenum Steel

AISI 4340
SAE 4340
40CrNiMo
SNCM439
EN 1.6511
36CrNiMo4

Boron Alloy Steel

10B22
10B21
15B21
15B25
20MnTiB
20Mn2B

35VB

40MnB

Bearing Steel

Bearing Steel

GCr15

AISI 52100
SAE 52100 · UNS G52986

SUJ2

100Cr6
EN 1.3505

GCr15SiMn

Spring Steel

Carbon Spring Steel

SAE 1065

SAE 1070

SAE 1075

SAE 1080

SAE 1095

65

70

75

80

65Mn

Silicon-Manganese Spring Steel

60Si2Mn
60Si2MnA
SUP6
SUP7

Chromium-Vanadium Spring Steel

50CrVA
SAE 6150
AISI 6150
SUP10

Stainless Spring Steel

AISI 301
SUS301
EN 1.4310
AISI 302
AISI 304
AISI 316
17-7 PH

Aluminum and Aluminum Alloys

Commercially Pure Aluminum

1050
1060
1070
1100

2xxx Series Aluminum

- 2024
- 2011
- 2014
- 2017

5xxx Series Aluminum

- 5052
- 5083
- 5754

6xxx Series Aluminum

- 6061
- 6061-T6
- 6063
- 6082
- 6082-T6

7xxx Series Aluminum

- 7075
- 7075-T6
- 7005
- 7050
- 7075-T73

Brass

Free-Cutting Brass

C36000
H62
HPb59-1
C3601
C3602
C3604
CuZn36Pb3
CuZn39Pb3
EN CW614N
EN CW617N
H65

Lead-Free Brass

C69300
C27450
CW510L
CW511L

Naval Brass

C46400
CuZn39Sn1

Bronze

Silicon Bronze

- C65500
- C65100
- C65600

Phosphor Bronze

- C51000
- C52100
- CuSn6
- CuSn8

Aluminum Bronze

- C95400
- C95500
- C63000
- CuAl10Ni5Fe4

Copper

Copper

- C11000
- T2
- C10100
- C10200
- C12200
- T1

TU1
TU2

Titanium and Titanium Alloys

Commercially Pure Titanium

Grade 2
Grade 1
Grade 3
Grade 4
TA1
TA2
TA3

Alpha-Beta Titanium Alloys

Grade 5
Ti-6Al-4V
TC4
UNS R56400

Low-Interstitial Grade

Grade 23
Ti-6Al-4V ELI
UNS R56407

Other Titanium Fastener Alloys

Ti-6Al-6V-2Sn
Ti-6Al-2Sn-4Zr-2Mo

Beta-C titanium

Ti-10V-2Fe-3Al

Nickel and Nickel Alloys

Commercially Pure Nickel

Nickel 200

UNS N02200

Nickel 201

UNS N02201

Inconel Alloys

Inconel 625
UNS N06625

Inconel 718
UNS N07718

Inconel 600
UNS N06600

Inconel 601
UNS N06601

Inconel 686
UNS N06686

Inconel X-750
UNS N07750

Monel Alloys

Monel 400
UNS N04400

Monel K-500
UNS N05500

Hastelloy Alloys

Hastelloy C-276
UNS N10276

Hastelloy C-22
UNS N06022

Hastelloy B-2
UNS N10665

Hastelloy B-3
UNS N10675

Hastelloy X
UNS N06002

Other Nickel Alloys

Alloy 20
UNS N08020

Alloy 625

Alloy 718

Alloy 825
UNS N08825

Alloy 925
UNS N09925

Iron-Nickel and High-Temperature Alloys

A286

A-286

UNS S66286

EN 1.4980

Invar

Invar 36

Alloy 36

UNS K93600

FeNi36

Alloy 42

Alloy 42

UNS K94100

FeNi42

Tool Steel and Specialty Hardened Steel

Tool Steel and Specialty Hardened Steel

AISI D2

AISI H13

SKD11

Cr12MoV

AISI O1

AISI A2

AISI S7

SKD61

9CrSi

Structural and Construction Steel

Structural and Construction Steel

ASTM A36

Q235B
Q355B
S355JR
Q235C
Q355C
S235JR
S275JR
S355J2

Applications & Industries

The sectors that buy Hex Nut to GB/T 41 / ISO 4034, and the duty each one buys them for. Stocked from M3 to M36.

Industries that specify Hex Nut

Maintenance & MRO **Replacements matched to the existing bolt class, thread and finish.**

Building services **Threaded rod, channel and suspension assemblies.**

Machine building & OEM **The clamping counter-face on studs and bolts throughout an assembly.**

Steel fabrication **Bolted structural and frame connections.**

Automotive & transport **Vibration-prone joints where the locking type is specified on the drawing.**

Typical applications

- **completing a bolted joint on a stud, rod or bolt**
- **locking an adjustment so it cannot drift**
- **joints re-torqued at a service interval**

Service conditions to specify against

Marine and coastal

Available in A4 (316) stainless for chloride exposure — coastal structures, pool halls, water treatment and deck hardware, where A2 will eventually pit.

High load

Supplied in ISO 898-1 property classes, so the joint can be designed to a stated proof load and tightened to a calculated torque rather than by feel.

Match the class

A nut below the bolt property class strips before the bolt reaches its own limit — pair class 8 nuts with 8.8 bolts, class 10 with 10.9.

Need help matching Hex Nut to your application? Send the assembly, the load and the environment with your enquiry and we will specify the size, material and finish against them.

Video: A4 (316) Stainless Steel Hex Nut

► Watch video: https://www.youtube.com/watch?v=i0oAENc3-dE(https://www.youtube.com/watch?v=i0oAENc3-dE)

304/316/A2/A4 Stainless Steel Socket Head Cap Screws

(https://www.youtube.com/watch?v=i0oAENc3-dE)(https://www.youtube.com/watch?v=i0oAENc3-dE)

Third-party video, selected automatically for this topic. It is not produced by Engineering Hardware and is not a specification source — use the tables on this page for dimensional data.

Inside the plant

Manufactured in our own plant

This part is cold-formed, threaded, heat-treated and finished in-house. The stages below are where its class and finish are actually decided.

01

Cold heading

Wire rod is drawn to size and cold-formed into blanks. Forming rather than cutting keeps the grain flow continuous around the head, which is where a bolt is most likely to fail.

Head dimensions and under-head radius checked at set-up and per shift.

02

Thread rolling

Threads are rolled between hardened dies rather than cut. Rolled threads are stronger in fatigue than cut threads and hold pitch and flank angle far more consistently across a batch.

Go / no-go ring gauges to ISO 965 tolerance class 6g.

03

Heat treatment

Quench-and-temper brings carbon and alloy steel to the property class ordered — 8.8, 10.9 or 12.9 — with the furnace charge tracked so a finished lot can be traced back to it.

Core hardness and tensile tested per lot to ISO 898-1.

04

Surface treatment

Zinc, zinc-nickel, hot-dip galvanizing, black oxide, phosphate and Dacromet, selected against the service environment rather than against the price list.

Coating thickness and neutral salt spray hours to ISO 9227.

Frequently Asked Questions

What's the service temperature limit for A4 Stainless Steel?

The practical service range is approx. -200 °C to +400 °C, subject to the property class and the joint.

Can A4 Stainless Steel replace plated alloy steel structurally?

Only at the standard strength classes — A2-70 / A4-80 are roughly equivalent to class 7 steel; A4-100 reaches class 8.8. For class 10.9 or 12.9 strength, plated alloy steel is required.

Are A4 Stainless Steel Hex Nut — GB/T 41 / ISO 4034 (Series 060) magnetic?

A4 Stainless Steel Hex Nut — GB/T 41 / ISO 4034 (Series 060) are largely non-magnetic.

What corrosion resistance do A4 Stainless Steel Hex Nut — GB/T 41 / ISO 4034 (Series 060) offer?

A4 Stainless Steel Hex Nut — GB/T 41 / ISO 4034 (Series 060) provide superior, including marine and chloride environments with a service range of approx. -200 °C to +400 °C, subject to the property class and the joint.

How do I request a quotation?

Use the technical drawing on this page to pick the exact configuration, then submit it with the quote form. We respond within one business day.

Related Pages

View the full Hex Nut — GB/T 41 / ISO 4034 (Series 060) page (https://engineeringhardware.com/fastener/cad-svg-060-hexnut/)

More Hex Nut — GB/T 41 / ISO 4034 (Series 060) Guides

- **A2 Stainless Steel Hex Nut — GB/T 41 / ISO 4034 (Series 060) (https://engineeringhardware.com/guide/material/a2-stainless-steel-cad-svg-060-hexnut/)**
- **Property Class 8.8 Steel Hex Nut — GB/T 41 / ISO 4034 (Series 060) (https://engineeringhardware.com/guide/material/grade-8-8-steel-cad-svg-060-hexnut/)**
- **Property Class 12.9 Steel Hex Nut — GB/T 41 / ISO 4034 (Series 060) (https://engineeringhardware.com/guide/material/grade-12-9-steel-cad-svg-060-hexnut/)**