

FKM (Viton®-type) AS568 O-Rings (Inch Series)

Engineering Hardware & Fasteners · engineeringhardware.com/guide/material/fkm-as568-o-rings-inch

[Fasteners/Seals AS568 O-Rings \(Inch Series\)](#)/FKM (Viton®-type) AS568 O-Rings (Inch Series)

Seals · AS 568

Temperature range, chemical and fluid compatibility, hardness and the full dimensional range for this compound.

FKM (Viton®-type) AS568 O-Rings (Inch Series) are supplied to fluoroelastomer, typically 75 Shore A. Corrosion behaviour is excellent resistance to heat, fuels, and most chemicals; poor with ketones and hot water/steam, the material is non-magnetic, and the usable service range is approx. -20 °C to +200 °C. In practice this grade is specified where temperature or chemical exposure exceeds nitrile.

Grade

fluoroelastomer, typically 75 Shore A

Corrosion resistance

Excellent resistance to heat, fuels, and most chemicals; poor with ketones and hot water/steam

Magnetic response

Non-magnetic

Service temperature

approx. -20 °C to +200 °C

Property values are typical for the grade. Certified mechanical test data is available on request for production orders.



FKM (Viton®-type) (fluoroelastomer, typically 75 Shore A) is specified where temperature or chemical exposure exceeds nitrile. When AS568 O-rings (inch series) are specified in this grade, the dimensions remain per AS 568; the material determines corrosion behavior (excellent resistance to heat, fuels, and most chemicals; poor with ketones and hot water/steam) and the service temperature range (approx. -20 °C to +200 °C). Both are covered below with the size table.

Why Choose FKM (Viton®-type) for AS568 O-Rings (Inch Series)

Specified where temperature or chemical exposure exceeds nitrile. For AS568 O-rings (inch series), this matters when excellent resistance to heat, fuels, and most chemicals; poor with ketones and hot water/steam is the primary requirement.

Mechanical & Physical Properties

Grade designation	fluoroelastomer, typically 75 Shore A
Magnetic response	Non-magnetic
Service temperature	approx. -20 °C to +200 °C
Corrosion characteristic	Excellent resistance to heat, fuels, and most chemicals; poor with ketones and hot water/steam

Galvanic & Galling Considerations

Galvanic and galling behavior do not apply to as568 o-rings (inch series) in FKM (Viton®-type) — the relevant compatibility questions are chemical: confirm the elastomer against the fluid, the temperature and any cleaning agents in service, and check the gland or groove dimensions give the intended compression on the section.

Comparable Grades

For as568 o-rings (inch series), consider NBR where the service is ordinary mineral oil and the cost matters, or EPDM for hot water and steam, which attacks FKM. Elastomer selection is decided by the medium, the temperature range and whether the seal is static or dynamic — not by strength.

Sizes of AS568 O-Rings (Inch Series) Available in FKM (Viton®-type)

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-001	0.029	0.74	0.040	1.02	1.42	AS 568
AS568-002	0.042	1.07	0.040	1.02	1.42	AS 568
AS568-003	0.056	1.42	0.040	1.02	1.42	AS 568
AS568-004	0.070	1.78	0.040	1.02	1.42	AS 568
AS568-005	0.101	2.57	0.040	1.02	1.42	AS 568
AS568-006	0.114	2.90	0.070	1.78	2.49	AS 568
AS568-007	0.145	3.68	0.070	1.78	2.49	AS 568
AS568-008	0.176	4.47	0.070	1.78	2.49	AS 568
AS568-009	0.208	5.28	0.070	1.78	2.49	AS 568
AS568-010	0.239	6.07	0.070	1.78	2.49	AS 568
AS568-011	0.301	7.65	0.070	1.78	2.49	AS 568
AS568-012	0.364	9.25	0.070	1.78	2.49	AS 568
AS568-013	0.426	10.82	0.070	1.78	2.49	AS 568
AS568-014	0.489	12.42	0.070	1.78	2.49	AS 568
AS568-015	0.551	14.00	0.070	1.78	2.49	AS 568
AS568-016	0.614	15.60	0.070	1.78	2.49	AS 568
AS568-017	0.676	17.17	0.070	1.78	2.49	AS 568
AS568-018	0.739	18.77	0.070	1.78	2.49	AS 568
AS568-019	0.801	20.35	0.070	1.78	2.49	AS 568
AS568-020	0.864	21.95	0.070	1.78	2.49	AS 568
AS568-021	0.926	23.52	0.070	1.78	2.49	AS 568
AS568-022	0.989	25.12	0.070	1.78	2.49	AS 568
AS568-023	1.051	26.70	0.070	1.78	2.49	AS 568
AS568-024	1.114	28.30	0.070	1.78	2.49	AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-025	1.176	29.87	0.070	1.78	2.49	AS 568
AS568-026	1.239	31.47	0.070	1.78	2.49	AS 568
AS568-027	1.301	33.05	0.070	1.78	2.49	AS 568
AS568-028	1.364	34.65	0.070	1.78	2.49	AS 568
AS568-029	1.489	37.82	0.070	1.78	2.49	AS 568
AS568-030	1.614	41.00	0.070	1.78	2.49	AS 568

Technical Drawing

Customize the parameters below — every spec field is editable, and the drawing redraws to match the values you choose. Changing the size will snap the other fields to that size's standard values; you can then override any individual value.

Sends the selected values to the quote form below.

Request a Quote

The form below follows the current technical drawing configuration. Change the drawing values above and the request details update automatically.

Dimensions & Specifications (AS 568)

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-001	0.029	0.74	0.040	1.02	1.42	AS 568
AS568-002	0.042	1.07	0.040	1.02	1.42	AS 568
AS568-003	0.056	1.42	0.040	1.02	1.42	AS 568
AS568-004	0.070	1.78	0.040	1.02	1.42	AS 568
AS568-005	0.101	2.57	0.040	1.02	1.42	AS 568
AS568-006	0.114	2.90	0.070	1.78	2.49	AS 568
AS568-007	0.145	3.68	0.070	1.78	2.49	AS 568
AS568-008	0.176	4.47	0.070	1.78	2.49	AS 568
AS568-009	0.208	5.28	0.070	1.78	2.49	AS 568
AS568-010	0.239	6.07	0.070	1.78	2.49	AS 568
AS568-011	0.301	7.65	0.070	1.78	2.49	AS 568
AS568-012	0.364	9.25	0.070	1.78	2.49	AS 568
AS568-013	0.426	10.82	0.070	1.78	2.49	AS 568
AS568-014	0.489	12.42	0.070	1.78	2.49	AS 568
AS568-015	0.551	14.00	0.070	1.78	2.49	AS 568
AS568-016	0.614	15.60	0.070	1.78	2.49	AS 568
AS568-017	0.676	17.17	0.070	1.78	2.49	AS 568
AS568-018	0.739	18.77	0.070	1.78	2.49	AS 568
AS568-019	0.801	20.35	0.070	1.78	2.49	AS 568
AS568-020	0.864	21.95	0.070	1.78	2.49	AS 568
AS568-021	0.926	23.52	0.070	1.78	2.49	AS 568
AS568-022	0.989	25.12	0.070	1.78	2.49	AS 568
AS568-023	1.051	26.70	0.070	1.78	2.49	AS 568
AS568-024	1.114	28.30	0.070	1.78	2.49	AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-025	1.176	29.87	0.070	1.78	2.49	AS 568
AS568-026	1.239	31.47	0.070	1.78	2.49	AS 568
AS568-027	1.301	33.05	0.070	1.78	2.49	AS 568
AS568-028	1.364	34.65	0.070	1.78	2.49	AS 568
AS568-029	1.489	37.82	0.070	1.78	2.49	AS 568
AS568-030	1.614	41.00	0.070	1.78	2.49	AS 568
AS568-031	1.739	44.17	0.070	1.78	2.49	AS 568
AS568-032	1.864	47.35	0.070	1.78	2.49	AS 568
AS568-033	1.989	50.52	0.070	1.78	2.49	AS 568
AS568-034	2.114	53.70	0.070	1.78	2.49	AS 568
AS568-035	2.239	56.87	0.070	1.78	2.49	AS 568
AS568-036	2.364	60.05	0.070	1.78	2.49	AS 568
AS568-037	2.489	63.22	0.070	1.78	2.49	AS 568
AS568-038	2.614	66.40	0.070	1.78	2.49	AS 568
AS568-039	2.739	69.57	0.070	1.78	2.49	AS 568
AS568-040	2.864	72.75	0.070	1.78	2.49	AS 568
AS568-041	2.989	75.92	0.070	1.78	2.49	AS 568
AS568-042	3.239	82.27	0.070	1.78	2.49	AS 568
AS568-043	3.489	88.62	0.070	1.78	2.49	AS 568
AS568-044	3.739	94.97	0.070	1.78	2.49	AS 568
AS568-045	3.989	101.32	0.070	1.78	2.49	AS 568
AS568-046	4.239	107.67	0.070	1.78	2.49	AS 568
AS568-047	4.489	114.02	0.070	1.78	2.49	AS 568
AS568-048	4.739	120.37	0.070	1.78	2.49	AS 568
AS568-049	4.989	126.72	0.070	1.78	2.49	AS 568
AS568-050	5.239	133.07	0.070	1.78	2.49	AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-102	0.049	1.24	0.103	2.62	3.66	AS 568
AS568-103	0.081	2.06	0.103	2.62	3.66	AS 568
AS568-104	0.112	2.84	0.103	2.62	3.66	AS 568
AS568-105	0.143	3.63	0.103	2.62	3.66	AS 568
AS568-106	0.174	4.42	0.103	2.62	3.66	AS 568
AS568-107	0.206	5.23	0.103	2.62	3.66	AS 568
AS568-108	0.237	6.02	0.103	2.62	3.66	AS 568
AS568-109	0.299	7.59	0.103	2.62	3.66	AS 568
AS568-110	0.362	9.19	0.103	2.62	3.66	AS 568
AS568-111	0.424	10.77	0.103	2.62	3.66	AS 568
AS568-112	0.487	12.37	0.103	2.62	3.66	AS 568
AS568-113	0.549	13.94	0.103	2.62	3.66	AS 568
AS568-114	0.612	15.54	0.103	2.62	3.66	AS 568
AS568-115	0.674	17.12	0.103	2.62	3.66	AS 568
AS568-116	0.737	18.72	0.103	2.62	3.66	AS 568
AS568-117	0.799	20.29	0.103	2.62	3.66	AS 568
AS568-118	0.862	21.89	0.103	2.62	3.66	AS 568
AS568-119	0.924	23.47	0.103	2.62	3.66	AS 568
AS568-120	0.987	25.07	0.103	2.62	3.66	AS 568
AS568-121	1.049	26.64	0.103	2.62	3.66	AS 568
AS568-122	1.112	28.24	0.103	2.62	3.66	AS 568
AS568-123	1.174	29.82	0.103	2.62	3.66	AS 568
AS568-124	1.237	31.42	0.103	2.62	3.66	AS 568
AS568-125	1.299	32.99	0.103	2.62	3.66	AS 568
AS568-126	1.362	34.59	0.103	2.62	3.66	AS 568
AS568-127	1.424	36.17	0.103	2.62	3.66	AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-128	1.487	37.77	0.103	2.62	3.66	AS 568
AS568-129	1.549	39.34	0.103	2.62	3.66	AS 568
AS568-130	1.612	40.94	0.103	2.62	3.66	AS 568
AS568-131	1.674	42.52	0.103	2.62	3.66	AS 568
AS568-132	1.737	44.12	0.103	2.62	3.66	AS 568
AS568-133	1.799	45.69	0.103	2.62	3.66	AS 568
AS568-134	1.862	47.29	0.103	2.62	3.66	AS 568
AS568-135	1.924	48.87	0.103	2.62	3.66	AS 568
AS568-136	1.987	50.47	0.103	2.62	3.66	AS 568
AS568-137	2.049	52.04	0.103	2.62	3.66	AS 568
AS568-138	2.112	53.64	0.103	2.62	3.66	AS 568
AS568-139	2.174	55.22	0.103	2.62	3.66	AS 568
AS568-140	2.237	56.82	0.103	2.62	3.66	AS 568

Video: FKM (Viton®-type) AS568 O-Rings (Inch Series)



► Watch video: <https://www.youtube.com/watch?v=Wf19pCZc2E0>

O-Ring Sizing Tools

Third-party video, selected automatically for this topic. It is not produced by Engineering Hardware and is not a specification source — use the tables on this page for dimensional data.

Inside the plant

Manufactured in our own plant

This part is cold-formed, threaded, heat-treated and finished in-house. The stages below are where its class and finish are actually decided.

1.



01

Cold heading

Wire rod is drawn to size and cold-formed into blanks. Forming rather than cutting keeps the grain flow continuous around the head, which is where a bolt is most likely to fail.

Head dimensions and under-head radius checked at set-up and per shift.



2.

02

Thread rolling

Threads are rolled between hardened dies rather than cut. Rolled threads are stronger in fatigue than cut threads and hold pitch and flank angle far more consistently across a batch.

Go / no-go ring gauges to ISO 965 tolerance class 6g.

3.



03

Heat treatment

Quench-and-temper brings carbon and alloy steel to the property class ordered — 8.8, 10.9 or 12.9 — with the furnace charge tracked so a finished lot can be traced back to it.

Core hardness and tensile tested per lot to ISO 898-1.

4.



04

Surface treatment

Zinc, zinc-nickel, hot-dip galvanizing, black oxide, phosphate and Dacromet, selected against the service environment rather than against the price list.

Coating thickness and neutral salt spray hours to ISO 9227.

Frequently Asked Questions

Can FKM (Viton®-type) replace stainless steel structurally?

No — stainless A2/A4 cannot match class 10.9 / 12.9 strength. Stainless is selected for corrosion, not raw strength.

Are FKM (Viton®-type) AS568 O-Rings (Inch Series) magnetic?

FKM (Viton®-type) AS568 O-Rings (Inch Series) are non-magnetic.

What corrosion resistance do FKM (Viton®-type) AS568 O-Rings (Inch Series) offer?

FKM (Viton®-type) AS568 O-Rings (Inch Series) provide excellent resistance to heat, fuels, and most chemicals; poor with ketones and hot water/steam with a service range of approx. -20 °C to +200 °C.

When should I move from fluoroelastomer, typically 75 Shore A to class 8.8 for AS568 O-Rings (Inch Series)?

Step up to class 8.8 when the joint preload approaches the proof load of the current class. The higher class adds preload at the same diameter, often saving size and weight.

How do I request a quotation?

Use the technical drawing on this page to pick the exact configuration, then submit it with the quote form. We respond within one business day.

Related Pages

[View the full AS568 O-Rings \(Inch Series\) page](#)

More AS568 O-Rings (Inch Series) Guides

- [NBR \(Nitrile\) AS568 O-Rings \(Inch Series\)](#)
- [EPDM AS568 O-Rings \(Inch Series\)](#)
- [Silicone \(VMQ\) AS568 O-Rings \(Inch Series\)](#)
- [PTFE AS568 O-Rings \(Inch Series\)](#)