

M14 Socket Head Cap Screws Dimensions

Engineering Hardware & Fasteners · engineeringhardware.com/guide/size/m14-socket-head-cap-screws

[Fasteners Screws/Socket Head Cap Screws](#)/M14 Socket Head Cap Screws Dimensions

Screws · ISO 4762 / DIN 912

Controlling dimensions to ISO 4762 / DIN 912, with clearance hole and tapping drill, spanner or drive size and tightening torque.

M14 Socket Head Cap Screws dimensions to ISO 4762 / DIN 912: head diameter 21 mm, head height 14 mm, coarse thread pitch 2 mm, clearance hole (ISO 273 medium) 15.5 mm. Tighten to approximately 135 Nm at property class 8.8 in a dry, as-supplied condition.

Head diameter

21 mm

Head height

14 mm

Coarse thread pitch

2 mm

Clearance hole (ISO 273 medium)

15.5 mm

Tightening torque (class 8.8)

135 Nm

Figures are nominal values from the governing standard. Confirm against the tolerance class for your application before machining or ordering.



M14 Socket Head Cap Screws (ISO 4762 / DIN 912) are specified by thread size, length and head dimensions. The M14 row from the standard is reproduced below, followed by the drill sizes, spanner size and torque values used when installing this size.

M14 Dimensional Row (ISO 4762 / DIN 912)

Size	Pitch (mm)	Head diameter dk (mm)	Head height k (mm)	Hex key s (mm)	Socket depth t min (mm)	Reference standard
M14	2.0	21.0	14.0	12.0	7.0	ISO 4762 / DIN 912

Spanner & Drive for M14 Socket Head Cap Screws

The hex socket for M14 Socket Head Cap Screws is shown in the spec table — use the matching Allen / hex key (an ISO 2936 hex key set covers the full range). A T-handle Allen key gives the best feel for setting preload by feel; for production work use a torque-controlled driver.

Hole Sizes for M14

Coarse-thread pitch (ISO 724)	2 mm
Through-hole / clearance (ISO 273 medium)	15.5 mm
Tapping drill, coarse thread	12 mm

Tightening Torque for M14

Class 8.8 (dry, $\sim\mu$ 0.125)	$\approx$ 135 Nm
Class 10.9 (dry, $\sim\mu$ 0.125)	$\approx$ 190 Nm
Class 12.9 (dry, $\sim\mu$ 0.125)	$\approx$ 230 Nm

Indicative dry-joint values. Lubrication can lower the required torque by 15–25%. Always confirm against the joint design, especially when going up a strength class.

Proof Load & Strength for M14

Tensile stress area A_s (ISO 898-1)	115 mm ²
Proof load, class 8.8	67 kN
Proof load, class 10.9	95 kN
Proof load, class 12.9	112 kN
Min. ultimate tensile, class 8.8	92 kN

Proof load = stress area $\times$ proof stress per ISO 898-1. Design joints so the working preload stays below the proof load of the selected class.

Common Applications for M14 Socket Head Cap Screws

M14 Socket Head Cap Screws are commonly specified for heavier machine assembly and equipment mounting.

Installation Tips for M14 Socket Head Cap Screws

- Use a quality Allen key fully seated in the socket — partial engagement is the most common cause of stripped sockets at this size.
- For countersunk and button-head variants, chamfer the through-hole to seat the head flush without preloading the head/shank fillet.

Mating Parts for M14

For M14, pair with a M14 hex nut (ISO 4032 / DIN 934) and, where used, a M14 flat washer (ISO 7089 / DIN 125A) under the head and under the nut.

Technical Drawing

Customize the parameters below — every spec field is editable, and the drawing redraws to match the values you choose.

Changing the size will snap the other fields to that size's standard values; you can then override any individual value.

Sends the selected values to the quote form below.

Request a Quote

The form below follows the current technical drawing configuration. Change the drawing values above and the request details update automatically.

Dimensions & Specifications (ISO 4762 / DIN 912)

Size	Pitch (mm)	Head diameter dk (mm)	Head height k (mm)	Hex key s (mm)	Socket depth t min (mm)	Reference standard
M1	0.25	1.9	1.0	0.7	0.5	ISO 4762 / DIN 912
M1.2	0.25	2.3	1.2	0.9	0.6	ISO 4762 / DIN 912
M1.4	0.3	2.6	1.4	1.0	0.7	ISO 4762 / DIN 912
M1.6	0.35	3.0	1.6	1.5	0.7	ISO 4762 / DIN 912
M2	0.4	3.8	2.0	1.5	1.0	ISO 4762 / DIN 912
M2.5	0.45	4.5	2.5	2.0	1.1	ISO 4762 / DIN 912
M3	0.5	5.5	3.0	2.5	1.3	ISO 4762 / DIN 912
M4	0.7	7.0	4.0	3.0	2.0	ISO 4762 / DIN 912
M5	0.8	8.5	5.0	4.0	2.5	ISO 4762 / DIN 912
M6	1.0	10.0	6.0	5.0	3.0	ISO 4762 / DIN 912
M8	1.25	13.0	8.0	6.0	4.0	ISO 4762 / DIN 912
M10	1.5	16.0	10.0	8.0	5.0	ISO 4762 / DIN 912
M12	1.75	18.0	12.0	10.0	6.0	ISO 4762 / DIN 912
M14	2.0	21.0	14.0	12.0	7.0	ISO 4762 / DIN 912
M16	2.0	24.0	16.0	14.0	8.0	ISO 4762 / DIN 912
M18	2.5	27.0	18.0	14.0	9.0	ISO 4762 / DIN 912
M20	2.5	30.0	20.0	17.0	10.0	ISO 4762 / DIN 912
M22	2.5	33.0	22.0	17.0	11.0	ISO 4762 / DIN 912
M24	3.0	36.0	24.0	19.0	12.0	ISO 4762 / DIN 912
M27	3.0	40.0	27.0	19.0	13.5	ISO 4762 / DIN 912
M30	3.5	45.0	30.0	22.0	15.5	ISO 4762 / DIN 912
M33	3.5	50.0	33.0	24.0	17.5	ISO 4762 / DIN 912
M36	4.0	54.0	36.0	27.0	19.0	ISO 4762 / DIN 912
M42	4.5	63.0	42.0	32.0	21.0	ISO 4762 / DIN 912

Size	Pitch (mm)	Head diameter dk (mm)	Head height k (mm)	Hex key s (mm)	Socket depth t min (mm)	Reference standard
M48	5.0	72.0	48.0	36.0	25.0	ISO 4762 / DIN 912

Materials & Grades

Select a material class to see the grades we supply it in. Each designation is listed with its ISO/EN, AISI/SAE, JIS and GB equivalents.

[Stainless Steel](#)
[38 Carbon Steel](#)
[66 Alloy Steel](#)
[41 Bearing Steel](#)
[5 Spring Steel](#)
[25 Aluminum and Aluminum Alloys](#)
[21 Brass](#)
[17 Bronze](#)
[11 Copper](#)
[8 Titanium and Titanium Alloys](#)
[18 Nickel and Nickel Alloys](#)
[22 Iron-Nickel and High-Temperature Alloys](#)
[10 Tool Steel and Specialty Hardened Steel](#)
[9 Structural and Construction Steel](#)

Stainless Steel

Austenitic Stainless Steel

- A1 AISI 303 · SAE 303 · SUS303 · EN 1.4305 · X8CrNiS18-9
- A2 AISI 304 · SAE 304 · SUS304 · EN 1.4301 · X5CrNi18-10 · 06Cr19Ni10
- 304L AISI 304L · SUS304L · EN 1.4307 · X2CrNi18-9 · 022Cr19Ni10
- 302 AISI 302 · SUS302 · EN 1.4310
- 305 AISI 305 · SUS305 · EN 1.4303
- A4 AISI 316 · SAE 316 · SUS316 · EN 1.4401 · X5CrNiMo17-12-2 · 06Cr17Ni12Mo2
- 316L AISI 316L · SUS316L · EN 1.4404 · X2CrNiMo17-12-2 · 022Cr17Ni12Mo2
- 321 AISI 321 · SUS321 · EN 1.4541 · X6CrNiTi18-10
- 310 / 310S AISI 310 · AISI 310S · SUS310S · EN 1.4845
- 302HQ AISI 302HQ
- A3
- A5
- 347 AISI 347 · SUS347 · EN 1.4550 · X6CrNiNb18-10
- 309 / 309S AISI 309 · AISI 309S · SUS309S

Martensitic Stainless Steel

- AISI 410 SUS410 · EN 1.4006 · X12Cr13 · 12Cr13
- AISI 420 SUS420J1 · SUS420J2 · EN 1.4021 · EN 1.4028 · 20Cr13 · 30Cr13
- AISI 431 SUS431 · EN 1.4057 · X17CrNi16-2
- C1
- C3
- C4

- AISI 440A
- AISI 440B
- AISI 440C SUS440C · EN 1.4125

Ferritic Stainless Steel

- AISI 430 SUS430 · EN 1.4016 · X6Cr17 · 10Cr17
- F1
- AISI 434
- AISI 444

Precipitation-Hardening Stainless Steel

- 17-4 PH AISI 630 · UNS S17400 · SUS630 · EN 1.4542 · X5CrNiCuNb16-4
- 15-5 PH UNS S15500
- 17-7 PH UNS S17700

Duplex and Super Duplex Stainless Steel

- Duplex 2205 UNS S31803 · UNS S32205 · EN 1.4462
- Super Duplex 2507 UNS S32750 · EN 1.4410
- D2
- D4
- D6
- D8
- Lean Duplex 2101 UNS S32101
- Super Duplex S32760 UNS S32760 · EN 1.4501

Carbon Steel

Low-Carbon Steel

- SAE 1006
- SAE 1008
- SAE 1010
- SAE 1018
- SAE 1020
- Q195
- Q235
- SAE 1012

- SAE 1015
- Q215
- ML08
- ML08AI
- ML10
- ML15
- ML20
- SWRCH6A
- SWRCH8A
- SWRCH10A
- SWRCH12A
- SWRCH15A
- SWRCH18A

Medium-Carbon Steel

- SAE 1035
- SAE 1045
- S45C
- C45
- SAE 1030
- SAE 1040
- SAE 1050
- 30
- 35
- 40
- 45
- 50
- S35C
- S40C
- S50C
- C35
- C40

High-Carbon Steel

- SAE 1060
- SAE 1070

- 65Mn
- SAE 1065
- SAE 1075
- SAE 1080
- SAE 1085
- SAE 1090
- SAE 1095
- 60
- 65
- 70
- 75
- 80
- 85

Cold-Heading Steel

- SWRCH22A
- 10B21
- SWRCH22K
- SWRCH25K
- SWRCH30K
- SWRCH35K
- SWRCH40K
- ML20Mn
- ML25
- ML30
- ML35
- ML40
- 15B25

Alloy Steel

Chromium Steel

- 40Cr
- 45Cr
- AISI 5140
- SAE 5140

- AISI 5120
- SAE 5120
- SCr420
- SCr440

Chromium-Molybdenum Steel

- 35CrMo
- 42CrMo
- AISI 4140
- SCM435
- SCM440
- 42CrMo4
- 30CrMo
- AISI 4130
- SAE 4130
- SAE 4140
- AISI 4142
- AISI 4145
- SCM415
- SCM420
- SCM445
- EN 1.7220
- EN 1.7225
- 25CrMo4
- 34CrMo4

Nickel-Chromium-Molybdenum Steel

- AISI 4340
- SAE 4340
- 40CrNiMo
- SNCM439
- EN 1.6511
- 36CrNiMo4

Boron Alloy Steel

- 10B22

- 10B21
- 15B21
- 15B25
- 20MnTiB
- 20Mn2B
- 35VB
- 40MnB

Bearing Steel

Bearing Steel

- GCr15
- AISI 52100 SAE 52100 · UNS G52986
- SUJ2
- 100Cr6 EN 1.3505
- GCr15SiMn

Spring Steel

Carbon Spring Steel

- SAE 1065
- SAE 1070
- SAE 1075
- SAE 1080
- SAE 1095
- 65
- 70
- 75
- 80
- 65Mn

Silicon-Manganese Spring Steel

- 60Si2Mn
- 60Si2MnA
- SUP6
- SUP7

Chromium-Vanadium Spring Steel

- 50CrVA
- SAE 6150
- AISI 6150
- SUP10

Stainless Spring Steel

- AISI 301
- SUS301
- EN 1.4310
- AISI 302
- AISI 304
- AISI 316
- 17-7 PH

Aluminum and Aluminum Alloys

Commercially Pure Aluminum

- 1050
- 1060
- 1070
- 1100

2xxx Series Aluminum

- 2024
- 2011
- 2014
- 2017

5xxx Series Aluminum

- 5052
- 5083
- 5754

6xxx Series Aluminum

- 6061
- 6061-T6
- 6063
- 6082
- 6082-T6

7xxx Series Aluminum

- 7075
- 7075-T6
- 7005
- 7050
- 7075-T73

Brass

Free-Cutting Brass

- C36000
- H62
- HPb59-1
- C3601
- C3602
- C3604
- CuZn36Pb3
- CuZn39Pb3
- EN CW614N
- EN CW617N
- H65

Lead-Free Brass

- C69300
- C27450
- CW510L
- CW511L

Naval Brass

- C46400
- CuZn39Sn1

Bronze

Silicon Bronze

- C65500
- C65100
- C65600

Phosphor Bronze

- C51000
- C52100
- CuSn6
- CuSn8

Aluminum Bronze

- C95400
- C95500
- C63000
- CuAl10Ni5Fe4

Copper

Copper

- C11000
- T2
- C10100
- C10200
- C12200
- T1
- TU1
- TU2

Titanium and Titanium Alloys

Commercially Pure Titanium

- Grade 2
- Grade 1
- Grade 3
- Grade 4
- TA1
- TA2
- TA3

Alpha-Beta Titanium Alloys

- Grade 5
- Ti-6Al-4V
- TC4
- UNS R56400

Low-Interstitial Grade

- Grade 23
- Ti-6Al-4V ELI
- UNS R56407

Other Titanium Fastener Alloys

- Ti-6Al-6V-2Sn
- Ti-6Al-2Sn-4Zr-2Mo
- Beta-C titanium
- Ti-10V-2Fe-3Al

Nickel and Nickel Alloys

Commercially Pure Nickel

- Nickel 200
- UNS N02200
- Nickel 201
- UNS N02201

Inconel Alloys

- Inconel 625 UNS N06625
- Inconel 718 UNS N07718
- Inconel 600 UNS N06600
- Inconel 601 UNS N06601
- Inconel 686 UNS N06686
- Inconel X-750 UNS N07750

Monel Alloys

- Monel 400 UNS N04400
- Monel K-500 UNS N05500

Hastelloy Alloys

- Hastelloy C-276 UNS N10276
- Hastelloy C-22 UNS N06022
- Hastelloy B-2 UNS N10665
- Hastelloy B-3 UNS N10675
- Hastelloy X UNS N06002

Other Nickel Alloys

- Alloy 20 UNS N08020
- Alloy 625
- Alloy 718
- Alloy 825 UNS N08825
- Alloy 925 UNS N09925

Iron-Nickel and High-Temperature Alloys

A286

- A-286
- UNS S66286
- EN 1.4980

Invar

- Invar 36

- Alloy 36
- UNS K93600
- FeNi36

Alloy 42

- Alloy 42
- UNS K94100
- FeNi42

Tool Steel and Specialty Hardened Steel

Tool Steel and Specialty Hardened Steel

- AISI D2
- AISI H13
- SKD11
- Cr12MoV
- AISI O1
- AISI A2
- AISI S7
- SKD61
- 9CrSi

Structural and Construction Steel

Structural and Construction Steel

- ASTM A36
- Q235B
- Q355B
- S355JR
- Q235C
- Q355C
- S235JR
- S275JR
- S355J2

Video: M14 Socket Head Cap Screws Dimensions

SOCKET HEAD CAP SCREW DIMENSION CHART

Dimensions of Hexagon and Spine Socket Head Cap Screws (1900 Series)

Nominal Size of Socket Screw Diameter	D Body Diameter		A Head Diameter		H Head Height		Hex Head Height	Hex Socket Width	J Hex Socket Depth	K Hexagon Width	L Thread L Gather Width
	Min.	Max.	Min.	Max.	Min.	Max.					
1/16	0.0625	0.0625	0.125	0.125	0.031	0.031	0.031	0.125	0.031	0.125	0.031
1/8	0.0787	0.0787	0.156	0.156	0.031	0.031	0.031	0.156	0.031	0.156	0.031
3/16	0.1094	0.1094	0.187	0.187	0.031	0.031	0.031	0.187	0.031	0.187	0.031
1/4	0.125	0.125	0.21	0.21	0.031	0.031	0.031	0.21	0.031	0.21	0.031
5/16	0.1562	0.1562	0.25	0.25	0.031	0.031	0.031	0.25	0.031	0.25	0.031
3/8	0.1875	0.1875	0.312	0.312	0.031	0.031	0.031	0.312	0.031	0.312	0.031
1/2	0.25	0.25	0.375	0.375	0.031	0.031	0.031	0.375	0.031	0.375	0.031
5/8	0.3125	0.3125	0.437	0.437	0.031	0.031	0.031	0.437	0.031	0.437	0.031
3/4	0.375	0.375	0.5	0.5	0.031	0.031	0.031	0.5	0.031	0.5	0.031
7/8	0.4375	0.4375	0.562	0.562	0.031	0.031	0.031	0.562	0.031	0.562	0.031
1	0.5	0.5	0.625	0.625	0.031	0.031	0.031	0.625	0.031	0.625	0.031
1 1/8	0.5625	0.5625	0.687	0.687	0.031	0.031	0.031	0.687	0.031	0.687	0.031
1 1/4	0.625	0.625	0.75	0.75	0.031	0.031	0.031	0.75	0.031	0.75	0.031
1 3/8	0.6875	0.6875	0.812	0.812	0.031	0.031	0.031	0.812	0.031	0.812	0.031
1 1/2	0.75	0.75	0.875	0.875	0.031	0.031	0.031	0.875	0.031	0.875	0.031
1 3/4	0.8125	0.8125	0.937	0.937	0.031	0.031	0.031	0.937	0.031	0.937	0.031
2	1.0	1.0	1.125	1.125	0.031	0.031	0.031	1.125	0.031	1.125	0.031
2 1/4	1.125	1.125	1.25	1.25	0.031	0.031	0.031	1.25	0.031	1.25	0.031
2 1/2	1.25	1.25	1.375	1.375	0.031	0.031	0.031	1.375	0.031	1.375	0.031
2 3/4	1.375	1.375	1.5	1.5	0.031	0.031	0.031	1.5	0.031	1.5	0.031
3	1.5	1.5	1.625	1.625	0.031	0.031	0.031	1.625	0.031	1.625	0.031
3 1/4	1.625	1.625	1.75	1.75	0.031	0.031	0.031	1.75	0.031	1.75	0.031
3 1/2	1.75	1.75	1.875	1.875	0.031	0.031	0.031	1.875	0.031	1.875	0.031
3 3/4	1.875	1.875	2.0	2.0	0.031	0.031	0.031	2.0	0.031	2.0	0.031
4	2.0	2.0	2.125	2.125	0.031	0.031	0.031	2.125	0.031	2.125	0.031
4 1/4	2.125	2.125	2.25	2.25	0.031	0.031	0.031	2.25	0.031	2.25	0.031
4 1/2	2.25	2.25	2.375	2.375	0.031	0.031	0.031	2.375	0.031	2.375	0.031
4 3/4	2.375	2.375	2.5	2.5	0.031	0.031	0.031	2.5	0.031	2.5	0.031
5	2.5	2.5	2.625	2.625	0.031	0.031	0.031	2.625	0.031	2.625	0.031
5 1/4	2.625	2.625	2.75	2.75	0.031	0.031	0.031	2.75	0.031	2.75	0.031
5 1/2	2.75	2.75	2.875	2.875	0.031	0.031	0.031	2.875	0.031	2.875	0.031
5 3/4	2.875	2.875	3.0	3.0	0.031	0.031	0.031	3.0	0.031	3.0	0.031
6	3.0	3.0	3.125	3.125	0.031	0.031	0.031	3.125	0.031	3.125	0.031
6 1/4	3.125	3.125	3.25	3.25	0.031	0.031	0.031	3.25	0.031	3.25	0.031
6 1/2	3.25	3.25	3.375	3.375	0.031	0.031	0.031	3.375	0.031	3.375	0.031
6 3/4	3.375	3.375	3.5	3.5	0.031	0.031	0.031	3.5	0.031	3.5	0.031
7	3.5	3.5	3.625	3.625	0.031	0.031	0.031	3.625	0.031	3.625	0.031
7 1/4	3.625	3.625	3.75	3.75	0.031	0.031	0.031	3.75	0.031	3.75	0.031
7 1/2	3.75	3.75	3.875	3.875	0.031	0.031	0.031	3.875	0.031	3.875	0.031
7 3/4	3.875	3.875	4.0	4.0	0.031	0.031	0.031	4.0	0.031	4.0	0.031
8	4.0	4.0	4.125	4.125	0.031	0.031	0.031	4.125	0.031	4.125	0.031
8 1/4	4.125	4.125	4.25	4.25	0.031	0.031	0.031	4.25	0.031	4.25	0.031
8 1/2	4.25	4.25	4.375	4.375	0.031	0.031	0.031	4.375	0.031	4.375	0.031
8 3/4	4.375	4.375	4.5	4.5	0.031	0.031	0.031	4.5	0.031	4.5	0.031
9	4.5	4.5	4.625	4.625	0.031	0.031	0.031	4.625	0.031	4.625	0.031
9 1/4	4.625	4.625	4.75	4.75	0.031	0.031	0.031	4.75	0.031	4.75	0.031
9 1/2	4.75	4.75	4.875	4.875	0.031	0.031	0.031	4.875	0.031	4.875	0.031
9 3/4	4.875	4.875	5.0	5.0	0.031	0.031	0.031	5.0	0.031	5.0	0.031
10	5.0	5.0	5.125	5.125	0.031	0.031	0.031	5.125	0.031	5.125	0.031
10 1/4	5.125	5.125	5.25	5.25	0.031	0.031	0.031	5.25	0.031	5.25	0.031
10 1/2	5.25	5.25	5.375	5.375	0.031	0.031	0.031	5.375	0.031	5.375	0.031
10 3/4	5.375	5.375	5.5	5.5	0.031	0.031	0.031	5.5	0.031	5.5	0.031
11	5.5	5.5	5.625	5.625	0.031	0.031	0.031	5.625	0.031	5.625	0.031
11 1/4	5.625	5.625	5.75	5.75	0.031	0.031	0.031	5.75	0.031	5.75	0.031
11 1/2	5.75	5.75	5.875	5.875	0.031	0.031	0.031	5.875	0.031	5.875	0.031
11 3/4	5.875	5.875	6.0	6.0	0.031	0.031	0.031	6.0	0.031	6.0	0.031
12	6.0	6.0	6.125	6.125	0.031	0.031	0.031	6.125	0.031	6.125	0.031
12 1/4	6.125	6.125	6.25	6.25	0.031	0.031	0.031	6.25	0.031	6.25	0.031
12 1/2	6.25	6.25	6.375	6.375	0.031	0.031	0.031	6.375	0.031	6.375	0.031
12 3/4	6.375	6.375	6.5	6.5	0.031	0.031	0.031	6.5	0.031	6.5	0.031
13	6.5	6.5	6.625	6.625	0.031	0.031	0.031	6.625	0.031	6.625	0.031
13 1/4	6.625	6.625	6.75	6.75	0.031	0.031	0.031	6.75	0.031	6.75	0.031
13 1/2	6.75	6.75	6.875	6.875	0.031	0.031	0.031	6.875	0.031	6.875	0.031
13 3/4	6.875	6.875	7.0	7.0	0.031	0.031	0.031	7.0	0.031	7.0	0.031
14	7.0	7.0	7.125	7.125	0.031	0.031	0.031	7.125	0.031	7.125	0.031
14 1/4	7.125	7.125	7.25	7.25	0.031	0.031	0.031	7.25	0.031	7.25	0.031
14 1/2	7.25	7.25	7.375	7.375	0.031	0.031	0.031	7.375	0.031	7.375	0.031
14 3/4	7.375	7.375	7.5	7.5	0.031	0.031	0.031	7.5	0.031	7.5	0.031
15	7.5	7.5	7.625	7.625	0.031	0.031	0.031	7.625	0.031	7.625	0.031
15 1/4	7.625	7.625	7.75	7.75	0.031	0.031	0.031	7.75	0.031	7.75	0.031
15 1/2	7.75	7.75	7.875	7.875	0.031	0.031	0.031	7.875	0.031	7.875	0.031
15 3/4	7.875	7.875	8.0	8.0	0.031	0.031	0.031	8.0	0.031	8.0	0.031
16	8.0	8.0	8.125	8.125	0.031	0.031	0.031	8.125	0.031	8.125	0.031
16 1/4	8.125	8.125	8.25	8.25	0.031	0.031	0.031	8.25	0.031	8.25	0.031
16 1/2	8.25	8.25	8.375	8.375	0.031	0.031	0.031	8.375	0.031	8.375	0.031
16 3/4	8.375	8.375	8.5	8.5	0.031	0.031	0.031	8.5	0.031	8.5	0.031
17	8.5	8.5	8.625	8.625	0.031	0.031	0.031	8.625	0.031	8.625	0.031
17 1/4	8.625	8.625	8.75	8.75	0.031	0.031	0.031	8.75	0.031	8.75	0.031
17 1/2	8.75	8.75	8.875	8.875	0.031	0.031	0.031	8.875	0.031	8.875	0.031
17 3/4	8.875	8.875	9.0	9.0	0.031	0.031	0.031	9.0	0.031	9.0	0.031
18	9.0	9.0	9.125	9.125	0.031	0.031	0.031	9.125	0.031	9.125	0.031
18 1/4	9.125	9.125	9.25	9.25	0.031	0.031	0.031	9.25	0.031	9.25	0.031
18 1/2	9.25	9.25	9.375	9.375	0.031	0.031	0.031	9.375	0.031	9.375	0.031
18 3/4	9.375	9.375	9.5	9.5	0.031	0.031	0.031	9.5	0.031	9.5	0.031
19	9.5	9.5	9.625	9.625	0.031	0.031	0.031	9.625	0.031	9.625	0.031
19 1/4	9.625	9.625	9.75	9.75	0.031	0.031	0.031	9.75	0.031	9.75	0.031
19 1/2	9.75	9.75	9.875	9.875	0.031	0.031	0.031	9.875	0.031	9.875	0.031
19 3/4	9.875	9.875	10.0	10.0	0.031	0.031	0.031	10.0	0.031	10.0	0.031
20	10.0	10.0	10.125	10.125	0.031	0.031	0.031	10.125	0.031	10.125	0.031
20 1/4	10.125	10.125	10.25	10.25	0.031	0.031	0.031	10.25	0.031	10.25	0.031
20 1/2	10.25	10.25	10.375	10.375	0.031	0.031	0.031	10.375	0.031	10.375	0.031
20 3/4	10.375	10.375	10.5	10.5	0.031	0.031	0.031	10.5	0.031	10.5	0.031
21	10.5	10.5	10.625	10.625	0.031	0.031	0.031	10.625	0.031	10.625	0.031
21 1/4	10.625	10.625	10.75	10.75	0.031	0.031	0.031	10.75	0.031	10.75	0.031
21 1/2	10.75	10.75	10.875	10.875	0.031	0.031	0.031	10.875	0.031	10.875	0.031
21 3/4	10.875	10.875	11.0	11.0	0.031	0.031	0.031	11.0	0.031	11.0	0.031
22	11.0	11.0	11.125	11.125	0.031	0.031	0.031	11.125	0.031	11.125	0.031
22 1/4	11.125	11.125	11.25	11.25	0.031	0.031	0.031	11.25	0.031	11.25	0.031
22 1/2	11.25	11.25	11.375	11.375	0.031	0.031	0.031	11.375	0.031	11.375	0.031
22 3/4	11.375	11.375	11.5	11.5	0.031	0.031	0.031	11.5</			

► Watch video: <https://www.youtube.com/watch?v=xyZdaLzarBQ>

Cap Screw Dimension Chart

Third-party video, selected automatically for this topic. It is not produced by Engineering Hardware and is not a specification source — use the tables on this page for dimensional data.

Inside the plant

Manufactured in our own plant

This part is cold-formed, threaded, heat-treated and finished in-house. The stages below are where its class and finish are actually decided.

1.



01

Cold heading

Wire rod is drawn to size and cold-formed into blanks. Forming rather than cutting keeps the grain flow continuous around the head, which is where a bolt is most likely to fail.

Head dimensions and under-head radius checked at set-up and per shift.



2.

02

Thread rolling

Threads are rolled between hardened dies rather than cut. Rolled threads are stronger in fatigue than cut threads and hold pitch and flank angle far more consistently across a batch.

Go / no-go ring gauges to ISO 965 tolerance class 6g.

3.



03

Heat treatment

Quench-and-temper brings carbon and alloy steel to the property class ordered — 8.8, 10.9 or 12.9 — with the furnace charge tracked so a finished lot can be traced back to it.

Core hardness and tensile tested per lot to ISO 898-1.

4.



04

Surface treatment

Zinc, zinc-nickel, hot-dip galvanizing, black oxide, phosphate and Dacromet, selected against the service environment rather than against the price list.

Coating thickness and neutral salt spray hours to ISO 9227.

Frequently Asked Questions

Which Allen key fits M14 Socket Head Cap Screws?

The hex-socket size for each row of Socket Head Cap Screws is shown in the spec table — use the matching Allen / hex key. An ISO 2936 set covers every size on this page.

How do I avoid stripping the socket on M14 Socket Head Cap Screws?

Fully seat the key in the socket, choose ball-end keys only for low-torque finishing work, and prefer a T-handle key when feel matters. For production use a torque-controlled driver.

What is the coarse-thread pitch of M14 for Socket Head Cap Screws?

For M14 the standard coarse pitch is 2 mm — this is the value used for Socket Head Cap Screws.

What torque do M14 class 8.8 Socket Head Cap Screws take?

A dry M14 class 8.8 joint takes about 135 Nm ($\approx$ 190 Nm for 10.9, $\approx$ 230 Nm for 12.9). Confirm against your joint design; lubrication reduces these values.

How do I request a quotation?

Use the technical drawing on this page to pick the exact configuration, then submit it with the quote form. We respond within one business day.

Related Pages

[View the full Socket Head Cap Screws page](#)

More Socket Head Cap Screws Guides

- [M1.6 Socket Head Cap Screws](#)
- [M2 Socket Head Cap Screws](#)
- [M2.5 Socket Head Cap Screws](#)
- [M3 Socket Head Cap Screws](#)
- [M4 Socket Head Cap Screws](#)
- [M5 Socket Head Cap Screws](#)
- [M6 Socket Head Cap Screws](#)
- [M8 Socket Head Cap Screws](#)