


M5 Torx Countersunk Head Screw Dimensions

Engineering Hardware & Fasteners · engineeringhardware.com/guide/size/m5-cad-svg-023-countersunk



M5 Torx Countersunk Head Screw dimensions to GB/T 2673 / ISO 14583: head diameter 9.2 mm, head height 2.5 mm, coarse thread pitch 0.8 mm, clearance hole (ISO 273 medium) 5.5 mm. Tighten to approximately 5.8 Nm at property class 8.8 in a dry, as-supplied condition.

Head diameter

9.2 mm

Head height

2.5 mm

Coarse thread pitch

0.8 mm

Clearance hole (ISO 273 medium)

5.5 mm

Tightening torque (class 8.8)

5.8 Nm

Figures are nominal values from the governing standard. Confirm against the tolerance class for your application before machining or ordering.



M5 is one of the standard coarse-thread sizes for torx countersunk head screw under GB/T 2673 / ISO 14583. The sections below reproduce the dimensional row, list the matching tools and hole sizes, and summarize where this size is normally specified.

M5 Dimensional Row (GB/T 2673 / ISO 14583)

Size	Pitch (mm)	Length L (mm)	Head diameter dk (mm)	Head height k (mm)	Cross recess	Countersink angle (deg)	Reference standard
M5	0.8	30	9.2	2.5	PH2	90	ISO 7046 / GB/T 819

Spanner & Drive for M5 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023)

The hex socket for M5 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023) is shown in the spec table — use the matching Allen / hex key (an ISO 2936 hex key set covers the full range). A T-handle Allen key gives the best feel for setting preload by feel; for production work use a torque-controlled driver.

Hole Sizes for M5

Coarse-thread pitch (ISO 724)	0.8 mm
Through-hole / clearance (ISO 273 medium)	5.5 mm
Tapping drill, coarse thread	4.2 mm

Tightening Torque for M5

Class 8.8 (dry, $\sim\mu$ 0.125)	$\approx$ 5.8 Nm
Class 10.9 (dry, $\sim\mu$ 0.125)	$\approx$ 8.1 Nm
Class 12.9 (dry, $\sim\mu$ 0.125)	$\approx$ 9.7 Nm

Indicative dry-joint values. Lubrication can lower the required torque by 15–25%. Always confirm against the joint design, especially when going up a strength class.

Proof Load & Strength for M5

Tensile stress area A_s (ISO 898-1)	14.2 mm ²
Proof load, class 8.8	8.2 kN
Proof load, class 10.9	11.8 kN
Proof load, class 12.9	13.8 kN
Min. ultimate tensile, class 8.8	11.4 kN

Proof load = stress area $\times$ proof stress per ISO 898-1. Design joints so the working preload stays below the proof load of the selected class.

M5 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023) Weight

A steel M5 torx countersunk head screw at the listed 30 mm length weighs approximately 16 g each — about 16 kg per 1,000 pieces. Stainless A2/A4 weighs roughly the same (density 7.9–8.0 g/cm³). Actual weight varies slightly with head form, thread and finish; use this figure for freight estimation only.

Common Applications for M5 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023)

M5 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023) are commonly specified for electronics, PCB hardware, optical mounts and small-scale machinery.

Installation Tips for M5 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023)

- Use a quality Allen key fully seated in the socket — partial engagement is the most common cause of stripped sockets at this size.
- For countersunk and button-head variants, chamfer the through-hole to seat the head flush without preloading the head/shank fillet.
- At M5 the joint is sensitive to over-torque — use a torque-limiting driver and check the head doesn't bury into a softer counterpart.

Mating Parts for M5

For M5, pair with a M5 hex nut (ISO 4032 / DIN 934) and, where used, a M5 flat washer (ISO 7089 / DIN 125A) under the head and under the nut.

Technical Drawing

Customize the parameters below — every spec field is editable, and the drawing redraws to match the values you choose. Changing the size will snap the other fields to that size's standard values; you can then override any individual value.

Sends the selected values to the quote form below.

Request a Quote

The form below follows the current technical drawing configuration. Change the drawing values above and the request details update automatically.

Dimensions & Specifications (GB/T 2673 / ISO 14583)

Size	Pitch (mm)	Length L (mm)	Head diameter dk (mm)	Head height k (mm)	Cross recess	Countersink angle (deg)	Reference standard
M3	0.5	20	5.6	1.65	PH1	90	ISO 7046 / GB/T 819
M4	0.7	25	7.5	2.2	PH2	90	ISO 7046 / GB/T 819
M5	0.8	30	9.2	2.5	PH2	90	ISO 7046 / GB/T 819
M6	1.0	40	11.0	3.0	PH3	90	ISO 7046 / GB/T 819
M8	1.25	50	14.5	4.0	PH3	90	ISO 7046 / GB/T 819
M10	1.5	60	18.0	5.0	PH4	90	ISO 7046 / GB/T 819
M12	1.75	80	22.0	6.0	PH4	90	ISO 7046 / GB/T 819
M14	2.0	80	25.0	7.0	PH4	90	ISO 7046 / GB/T 819
M16	2.0	100	29.0	8.0	PH4	90	ISO 7046 / GB/T 819
M18	2.5	100	33.0	9.0	PH4	90	ISO 7046 / GB/T 819
M20	2.5	120	36.5	10.0	PH4	90	ISO 7046 / GB/T 819
M24	3.0	150	43.5	12.0	PH4	90	ISO 7046 / GB/T 819

Materials & Grades

Select a material class to see the grades we supply it in. Each designation is listed with its ISO/EN, AISI/SAE, JIS and GB equivalents.

[Stainless Steel](#)
[38 Carbon Steel](#)
[66 Alloy Steel](#)
[41 Bearing Steel](#)
[5 Spring Steel](#)
[25 Aluminum and Aluminum Alloys](#)
[21 Brass](#)
[17 Bronze](#)
[11 Copper](#)
[8 Titanium and Titanium Alloys](#)
[18 Nickel and Nickel Alloys](#)
[22 Iron-Nickel and High-Temperature Alloys](#)
[10 Tool Steel](#)
[and](#)

Specialty Hardened Steel9 Structural and Construction Steel9

Stainless Steel

Austenitic Stainless Steel

- A1 AISI 303 · SAE 303 · SUS303 · EN 1.4305 · X8CrNiS18-9
- A2 AISI 304 · SAE 304 · SUS304 · EN 1.4301 · X5CrNi18-10 · 06Cr19Ni10
- 304L AISI 304L · SUS304L · EN 1.4307 · X2CrNi18-9 · 022Cr19Ni10
- 302 AISI 302 · SUS302 · EN 1.4310
- 305 AISI 305 · SUS305 · EN 1.4303
- A4 AISI 316 · SAE 316 · SUS316 · EN 1.4401 · X5CrNiMo17-12-2 · 06Cr17Ni12Mo2
- 316L AISI 316L · SUS316L · EN 1.4404 · X2CrNiMo17-12-2 · 022Cr17Ni12Mo2
- 321 AISI 321 · SUS321 · EN 1.4541 · X6CrNiTi18-10
- 310 / 310S AISI 310 · AISI 310S · SUS310S · EN 1.4845
- 302HQ AISI 302HQ
- A3
- A5
- 347 AISI 347 · SUS347 · EN 1.4550 · X6CrNiNb18-10
- 309 / 309S AISI 309 · AISI 309S · SUS309S

Martensitic Stainless Steel

- AISI 410 SUS410 · EN 1.4006 · X12Cr13 · 12Cr13
- AISI 420 SUS420J1 · SUS420J2 · EN 1.4021 · EN 1.4028 · 20Cr13 · 30Cr13
- AISI 431 SUS431 · EN 1.4057 · X17CrNi16-2
- C1
- C3
- C4
- AISI 440A
- AISI 440B
- AISI 440C SUS440C · EN 1.4125

Ferritic Stainless Steel

- AISI 430 SUS430 · EN 1.4016 · X6Cr17 · 10Cr17
- F1
- AISI 434
- AISI 444

Precipitation-Hardening Stainless Steel

- 17-4 PH AISI 630 · UNS S17400 · SUS630 · EN 1.4542 · X5CrNiCuNb16-4
- 15-5 PH UNS S15500
- 17-7 PH UNS S17700

Duplex and Super Duplex Stainless Steel

- Duplex 2205 UNS S31803 · UNS S32205 · EN 1.4462
- Super Duplex 2507 UNS S32750 · EN 1.4410
- D2
- D4
- D6
- D8
- Lean Duplex 2101 UNS S32101
- Super Duplex S32760 UNS S32760 · EN 1.4501

Carbon Steel

Low-Carbon Steel

- SAE 1006
- SAE 1008
- SAE 1010
- SAE 1018
- SAE 1020
- Q195
- Q235
- SAE 1012
- SAE 1015
- Q215
- ML08
- ML08Al
- ML10
- ML15
- ML20
- SWRCH6A
- SWRCH8A

- SWRCH10A
- SWRCH12A
- SWRCH15A
- SWRCH18A

Medium-Carbon Steel

- SAE 1035
- SAE 1045
- S45C
- C45
- SAE 1030
- SAE 1040
- SAE 1050
- 30
- 35
- 40
- 45
- 50
- S35C
- S40C
- S50C
- C35
- C40

High-Carbon Steel

- SAE 1060
- SAE 1070
- 65Mn
- SAE 1065
- SAE 1075
- SAE 1080
- SAE 1085
- SAE 1090
- SAE 1095
- 60
- 65

- 70
- 75
- 80
- 85

Cold-Heading Steel

- SWRCH22A
- 10B21
- SWRCH22K
- SWRCH25K
- SWRCH30K
- SWRCH35K
- SWRCH40K
- ML20Mn
- ML25
- ML30
- ML35
- ML40
- 15B25

Alloy Steel

Chromium Steel

- 40Cr
- 45Cr
- AISI 5140
- SAE 5140
- AISI 5120
- SAE 5120
- SCr420
- SCr440

Chromium-Molybdenum Steel

- 35CrMo
- 42CrMo
- AISI 4140

- SCM435
- SCM440
- 42CrMo4
- 30CrMo
- AISI 4130
- SAE 4130
- SAE 4140
- AISI 4142
- AISI 4145
- SCM415
- SCM420
- SCM445
- EN 1.7220
- EN 1.7225
- 25CrMo4
- 34CrMo4

Nickel-Chromium-Molybdenum Steel

- AISI 4340
- SAE 4340
- 40CrNiMo
- SNCM439
- EN 1.6511
- 36CrNiMo4

Boron Alloy Steel

- 10B22
- 10B21
- 15B21
- 15B25
- 20MnTiB
- 20Mn2B
- 35VB
- 40MnB

Bearing Steel

Bearing Steel

- GCr15
- AISI 52100 SAE 52100 · UNS G52986
- SUJ2
- 100Cr6 EN 1.3505
- GCr15SiMn

Spring Steel

Carbon Spring Steel

- SAE 1065
- SAE 1070
- SAE 1075
- SAE 1080
- SAE 1095
- 65
- 70
- 75
- 80
- 65Mn

Silicon-Manganese Spring Steel

- 60Si2Mn
- 60Si2MnA
- SUP6
- SUP7

Chromium-Vanadium Spring Steel

- 50CrVA
- SAE 6150
- AISI 6150
- SUP10

Stainless Spring Steel

- AISI 301
- SUS301
- EN 1.4310
- AISI 302
- AISI 304
- AISI 316
- 17-7 PH

Aluminum and Aluminum Alloys

Commercially Pure Aluminum

- 1050
- 1060
- 1070
- 1100

2xxx Series Aluminum

- 2024
- 2011
- 2014
- 2017

5xxx Series Aluminum

- 5052
- 5083
- 5754

6xxx Series Aluminum

- 6061
- 6061-T6
- 6063
- 6082
- 6082-T6

7xxx Series Aluminum

- 7075
- 7075-T6
- 7005
- 7050
- 7075-T73

Brass

Free-Cutting Brass

- C36000
- H62
- HPb59-1
- C3601
- C3602
- C3604
- CuZn36Pb3
- CuZn39Pb3
- EN CW614N
- EN CW617N
- H65

Lead-Free Brass

- C69300
- C27450
- CW510L
- CW511L

Naval Brass

- C46400
- CuZn39Sn1

Bronze

Silicon Bronze

- C65500
- C65100
- C65600

Phosphor Bronze

- C51000
- C52100
- CuSn6
- CuSn8

Aluminum Bronze

- C95400
- C95500
- C63000
- CuAl10Ni5Fe4

Copper

Copper

- C11000
- T2
- C10100
- C10200
- C12200
- T1
- TU1
- TU2

Titanium and Titanium Alloys

Commercially Pure Titanium

- Grade 2

- Grade 1
- Grade 3
- Grade 4
- TA1
- TA2
- TA3

Alpha-Beta Titanium Alloys

- Grade 5
- Ti-6Al-4V
- TC4
- UNS R56400

Low-Interstitial Grade

- Grade 23
- Ti-6Al-4V ELI
- UNS R56407

Other Titanium Fastener Alloys

- Ti-6Al-6V-2Sn
- Ti-6Al-2Sn-4Zr-2Mo
- Beta-C titanium
- Ti-10V-2Fe-3Al

Nickel and Nickel Alloys

Commercially Pure Nickel

- Nickel 200
- UNS N02200
- Nickel 201
- UNS N02201

Inconel Alloys

- Inconel 625 UNS N06625
- Inconel 718 UNS N07718
- Inconel 600 UNS N06600

- Inconel 601 UNS N06601
- Inconel 686 UNS N06686
- Inconel X-750 UNS N07750

Monel Alloys

- Monel 400 UNS N04400
- Monel K-500 UNS N05500

Hastelloy Alloys

- Hastelloy C-276 UNS N10276
- Hastelloy C-22 UNS N06022
- Hastelloy B-2 UNS N10665
- Hastelloy B-3 UNS N10675
- Hastelloy X UNS N06002

Other Nickel Alloys

- Alloy 20 UNS N08020
- Alloy 625
- Alloy 718
- Alloy 825 UNS N08825
- Alloy 925 UNS N09925

Iron-Nickel and High-Temperature Alloys

A286

- A-286
- UNS S66286
- EN 1.4980

Invar

- Invar 36
- Alloy 36
- UNS K93600
- FeNi36

Alloy 42

- Alloy 42
- UNS K94100
- FeNi42

Tool Steel and Specialty Hardened Steel

Tool Steel and Specialty Hardened Steel

- AISI D2
- AISI H13
- SKD11
- Cr12MoV
- AISI O1
- AISI A2
- AISI S7
- SKD61
- 9CrSi

Structural and Construction Steel

Structural and Construction Steel

- ASTM A36
- Q235B
- Q355B
- S355JR
- Q235C
- Q355C
- S235JR
- S275JR
- S355J2

Video: M5 Torx Countersunk Head Screw Dimensions



► Watch video: <https://www.youtube.com/watch?v=LtVFHht2Vbk>

Third-party video, selected automatically for this topic. It is not produced by Engineering Hardware and is not a specification source — use the tables on this page for dimensional data.

Inside the plant

Manufactured in our own plant

This part is cold-formed, threaded, heat-treated and finished in-house. The stages below are where its class and finish are actually decided.

1.



01

Cold heading

Wire rod is drawn to size and cold-formed into blanks. Forming rather than cutting keeps the grain flow continuous around the head, which is where a bolt is most likely to fail.

Head dimensions and under-head radius checked at set-up and per shift.



2.

02

Thread rolling

Threads are rolled between hardened dies rather than cut. Rolled threads are stronger in fatigue than cut threads and hold pitch and flank angle far more consistently across a batch.

Go / no-go ring gauges to ISO 965 tolerance class 6g.

3.



03

Heat treatment

Quench-and-temper brings carbon and alloy steel to the property class ordered — 8.8, 10.9 or 12.9 — with the furnace charge tracked so a finished lot can be traced back to it.

Core hardness and tensile tested per lot to ISO 898-1.

4.



04

Surface treatment

Zinc, zinc-nickel, hot-dip galvanizing, black oxide, phosphate and Dacromet, selected against the service environment rather than against the price list.

Coating thickness and neutral salt spray hours to ISO 9227.

Frequently Asked Questions

How do I avoid stripping the socket on M5 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023)?

Fully seat the key in the socket, choose ball-end keys only for low-torque finishing work, and prefer a T-handle key when feel matters. For production use a torque-controlled driver.

What is the coarse-thread pitch of M5 for Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023)?

For M5 the standard coarse pitch is 0.8 mm — this is the value used for Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023).

What torque do M5 class 8.8 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023) take?

A dry M5 class 8.8 joint takes about 5.8 Nm (≈ 8.1 Nm for 10.9, ≈ 9.7 Nm for 12.9). Confirm against your joint design; lubrication reduces these values.

What clearance and tapping drill suit M5?

Use a 5.5 mm clearance hole (ISO 273 medium) for through-fixing, or a 4.2 mm tapping drill for a coarse M5 thread.

How do I request a quotation?

Use the technical drawing on this page to pick the exact configuration, then submit it with the quote form. We respond within one business day.

Related Pages

[View the full Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 \(Series 023\) page](#)

More Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 (Series 023) Guides

- [M3 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 \(Series 023\)](#)
- [M4 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 \(Series 023\)](#)
- [M6 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 \(Series 023\)](#)
- [M8 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 \(Series 023\)](#)
- [M10 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 \(Series 023\)](#)
- [M12 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 \(Series 023\)](#)
- [M14 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 \(Series 023\)](#)
- [M16 Torx Countersunk Head Screw — GB/T 2673 / ISO 14583 \(Series 023\)](#)