

AS 568 AS568 O-Rings (Inch Series) Specification

Engineering Hardware & Fasteners · engineeringhardware.com/guide/standard/as-568-as568-o-rings-inch

Fasteners Seals AS568 O-Rings (Inch Series) AS 568 AS568 O-Rings (Inch Series) Specification

Seals · AS 568

Dimensional table, tolerance classes and the DIN / ISO / ASME parts that supersede or match this standard.

AS 568 specifies the dimensions and tolerances for as568 o-rings (inch series). The full dimensional table is reproduced below, followed by the DIN, ISO and ASME parts that match or supersede it.

Standard

AS 568

Product

AS568 O-Rings (Inch Series)

Governing standards

AS 568

Equivalence between national standards is dimensional, not always metallurgical. Check the property class separately when substituting.



For as568 o-rings (inch series), AS 568 is the governing document for the dimensions listed below. Mechanical and performance requirements for this part family are set by its own standards, not by the bolt and screw property-class documents.

AS 568 — Scope

AS 568 specifies the dimensional requirements for as568 o-rings (inch series). Material, surface condition and any performance rating are set by separate documents specific to this part family — ISO 898-1 and ISO 898-2, which govern bolt and nut property classes, do not apply here.

Tolerance & Product Grades

Tolerances for as568 o-rings (inch series) are given as limits on the individual dimensions in the table rather than as a fastener product grade. Where a general-tolerance class is cited on the drawing instead, it applies to the dimensions not otherwise toleranced.

Dimensions Specified by AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-001	0.029	0.74	0.040	1.02	1.42	AS 568
AS568-002	0.042	1.07	0.040	1.02	1.42	AS 568
AS568-003	0.056	1.42	0.040	1.02	1.42	AS 568
AS568-004	0.070	1.78	0.040	1.02	1.42	AS 568
AS568-005	0.101	2.57	0.040	1.02	1.42	AS 568
AS568-006	0.114	2.90	0.070	1.78	2.49	AS 568
AS568-007	0.145	3.68	0.070	1.78	2.49	AS 568
AS568-008	0.176	4.47	0.070	1.78	2.49	AS 568
AS568-009	0.208	5.28	0.070	1.78	2.49	AS 568
AS568-010	0.239	6.07	0.070	1.78	2.49	AS 568
AS568-011	0.301	7.65	0.070	1.78	2.49	AS 568
AS568-012	0.364	9.25	0.070	1.78	2.49	AS 568
AS568-013	0.426	10.82	0.070	1.78	2.49	AS 568
AS568-014	0.489	12.42	0.070	1.78	2.49	AS 568
AS568-015	0.551	14.00	0.070	1.78	2.49	AS 568
AS568-016	0.614	15.60	0.070	1.78	2.49	AS 568
AS568-017	0.676	17.17	0.070	1.78	2.49	AS 568
AS568-018	0.739	18.77	0.070	1.78	2.49	AS 568
AS568-019	0.801	20.35	0.070	1.78	2.49	AS 568
AS568-020	0.864	21.95	0.070	1.78	2.49	AS 568
AS568-021	0.926	23.52	0.070	1.78	2.49	AS 568
AS568-022	0.989	25.12	0.070	1.78	2.49	AS 568
AS568-023	1.051	26.70	0.070	1.78	2.49	AS 568
AS568-024	1.114	28.30	0.070	1.78	2.49	AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-025	1.176	29.87	0.070	1.78	2.49	AS 568
AS568-026	1.239	31.47	0.070	1.78	2.49	AS 568
AS568-027	1.301	33.05	0.070	1.78	2.49	AS 568
AS568-028	1.364	34.65	0.070	1.78	2.49	AS 568
AS568-029	1.489	37.82	0.070	1.78	2.49	AS 568
AS568-030	1.614	41.00	0.070	1.78	2.49	AS 568
AS568-031	1.739	44.17	0.070	1.78	2.49	AS 568
AS568-032	1.864	47.35	0.070	1.78	2.49	AS 568
AS568-033	1.989	50.52	0.070	1.78	2.49	AS 568
AS568-034	2.114	53.70	0.070	1.78	2.49	AS 568
AS568-035	2.239	56.87	0.070	1.78	2.49	AS 568
AS568-036	2.364	60.05	0.070	1.78	2.49	AS 568
AS568-037	2.489	63.22	0.070	1.78	2.49	AS 568
AS568-038	2.614	66.40	0.070	1.78	2.49	AS 568
AS568-039	2.739	69.57	0.070	1.78	2.49	AS 568
AS568-040	2.864	72.75	0.070	1.78	2.49	AS 568
AS568-041	2.989	75.92	0.070	1.78	2.49	AS 568
AS568-042	3.239	82.27	0.070	1.78	2.49	AS 568
AS568-043	3.489	88.62	0.070	1.78	2.49	AS 568
AS568-044	3.739	94.97	0.070	1.78	2.49	AS 568
AS568-045	3.989	101.32	0.070	1.78	2.49	AS 568
AS568-046	4.239	107.67	0.070	1.78	2.49	AS 568
AS568-047	4.489	114.02	0.070	1.78	2.49	AS 568
AS568-048	4.739	120.37	0.070	1.78	2.49	AS 568
AS568-049	4.989	126.72	0.070	1.78	2.49	AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-050	5.239	133.07	0.070	1.78	2.49	AS 568
AS568-102	0.049	1.24	0.103	2.62	3.66	AS 568
AS568-103	0.081	2.06	0.103	2.62	3.66	AS 568
AS568-104	0.112	2.84	0.103	2.62	3.66	AS 568
AS568-105	0.143	3.63	0.103	2.62	3.66	AS 568
AS568-106	0.174	4.42	0.103	2.62	3.66	AS 568
AS568-107	0.206	5.23	0.103	2.62	3.66	AS 568
AS568-108	0.237	6.02	0.103	2.62	3.66	AS 568
AS568-109	0.299	7.59	0.103	2.62	3.66	AS 568
AS568-110	0.362	9.19	0.103	2.62	3.66	AS 568
AS568-111	0.424	10.77	0.103	2.62	3.66	AS 568
AS568-112	0.487	12.37	0.103	2.62	3.66	AS 568
AS568-113	0.549	13.94	0.103	2.62	3.66	AS 568
AS568-114	0.612	15.54	0.103	2.62	3.66	AS 568
AS568-115	0.674	17.12	0.103	2.62	3.66	AS 568
AS568-116	0.737	18.72	0.103	2.62	3.66	AS 568
AS568-117	0.799	20.29	0.103	2.62	3.66	AS 568
AS568-118	0.862	21.89	0.103	2.62	3.66	AS 568
AS568-119	0.924	23.47	0.103	2.62	3.66	AS 568
AS568-120	0.987	25.07	0.103	2.62	3.66	AS 568
AS568-121	1.049	26.64	0.103	2.62	3.66	AS 568
AS568-122	1.112	28.24	0.103	2.62	3.66	AS 568
AS568-123	1.174	29.82	0.103	2.62	3.66	AS 568
AS568-124	1.237	31.42	0.103	2.62	3.66	AS 568
AS568-125	1.299	32.99	0.103	2.62	3.66	AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-126	1.362	34.59	0.103	2.62	3.66	AS 568
AS568-127	1.424	36.17	0.103	2.62	3.66	AS 568
AS568-128	1.487	37.77	0.103	2.62	3.66	AS 568
AS568-129	1.549	39.34	0.103	2.62	3.66	AS 568
AS568-130	1.612	40.94	0.103	2.62	3.66	AS 568
AS568-131	1.674	42.52	0.103	2.62	3.66	AS 568
AS568-132	1.737	44.12	0.103	2.62	3.66	AS 568
AS568-133	1.799	45.69	0.103	2.62	3.66	AS 568
AS568-134	1.862	47.29	0.103	2.62	3.66	AS 568
AS568-135	1.924	48.87	0.103	2.62	3.66	AS 568
AS568-136	1.987	50.47	0.103	2.62	3.66	AS 568
AS568-137	2.049	52.04	0.103	2.62	3.66	AS 568
AS568-138	2.112	53.64	0.103	2.62	3.66	AS 568
AS568-139	2.174	55.22	0.103	2.62	3.66	AS 568
AS568-140	2.237	56.82	0.103	2.62	3.66	AS 568

Equivalent Standards

Where direct equivalents exist (ISO ↔ DIN, ISO ↔ ASME), they are listed on the parent AS568 O-Rings (Inch Series) page. Always confirm against the dimensions on this page, since some "equivalent" standards differ in tolerances and head geometry.

When to Specify AS 568

Choose AS 568 for international engineering work and OEM supply where ISO standards are the contractual reference. It is the default modern specification for as568 o-rings (inch series).

Technical Drawing

Customize the parameters below — every spec field is editable, and the drawing redraws to match the values you choose. Changing the size will snap the other fields to that size's standard values; you can then override any individual value.

Sends the selected values to the quote form below.

Request a Quote

The form below follows the current technical drawing configuration. Change the drawing values above and the request details update automatically.

Dimensions & Specifications (AS 568)

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-001	0.029	0.74	0.040	1.02	1.42	AS 568
AS568-002	0.042	1.07	0.040	1.02	1.42	AS 568
AS568-003	0.056	1.42	0.040	1.02	1.42	AS 568
AS568-004	0.070	1.78	0.040	1.02	1.42	AS 568
AS568-005	0.101	2.57	0.040	1.02	1.42	AS 568
AS568-006	0.114	2.90	0.070	1.78	2.49	AS 568
AS568-007	0.145	3.68	0.070	1.78	2.49	AS 568
AS568-008	0.176	4.47	0.070	1.78	2.49	AS 568
AS568-009	0.208	5.28	0.070	1.78	2.49	AS 568
AS568-010	0.239	6.07	0.070	1.78	2.49	AS 568
AS568-011	0.301	7.65	0.070	1.78	2.49	AS 568
AS568-012	0.364	9.25	0.070	1.78	2.49	AS 568
AS568-013	0.426	10.82	0.070	1.78	2.49	AS 568
AS568-014	0.489	12.42	0.070	1.78	2.49	AS 568
AS568-015	0.551	14.00	0.070	1.78	2.49	AS 568
AS568-016	0.614	15.60	0.070	1.78	2.49	AS 568
AS568-017	0.676	17.17	0.070	1.78	2.49	AS 568
AS568-018	0.739	18.77	0.070	1.78	2.49	AS 568
AS568-019	0.801	20.35	0.070	1.78	2.49	AS 568
AS568-020	0.864	21.95	0.070	1.78	2.49	AS 568
AS568-021	0.926	23.52	0.070	1.78	2.49	AS 568
AS568-022	0.989	25.12	0.070	1.78	2.49	AS 568
AS568-023	1.051	26.70	0.070	1.78	2.49	AS 568
AS568-024	1.114	28.30	0.070	1.78	2.49	AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-025	1.176	29.87	0.070	1.78	2.49	AS 568
AS568-026	1.239	31.47	0.070	1.78	2.49	AS 568
AS568-027	1.301	33.05	0.070	1.78	2.49	AS 568
AS568-028	1.364	34.65	0.070	1.78	2.49	AS 568
AS568-029	1.489	37.82	0.070	1.78	2.49	AS 568
AS568-030	1.614	41.00	0.070	1.78	2.49	AS 568
AS568-031	1.739	44.17	0.070	1.78	2.49	AS 568
AS568-032	1.864	47.35	0.070	1.78	2.49	AS 568
AS568-033	1.989	50.52	0.070	1.78	2.49	AS 568
AS568-034	2.114	53.70	0.070	1.78	2.49	AS 568
AS568-035	2.239	56.87	0.070	1.78	2.49	AS 568
AS568-036	2.364	60.05	0.070	1.78	2.49	AS 568
AS568-037	2.489	63.22	0.070	1.78	2.49	AS 568
AS568-038	2.614	66.40	0.070	1.78	2.49	AS 568
AS568-039	2.739	69.57	0.070	1.78	2.49	AS 568
AS568-040	2.864	72.75	0.070	1.78	2.49	AS 568
AS568-041	2.989	75.92	0.070	1.78	2.49	AS 568
AS568-042	3.239	82.27	0.070	1.78	2.49	AS 568
AS568-043	3.489	88.62	0.070	1.78	2.49	AS 568
AS568-044	3.739	94.97	0.070	1.78	2.49	AS 568
AS568-045	3.989	101.32	0.070	1.78	2.49	AS 568
AS568-046	4.239	107.67	0.070	1.78	2.49	AS 568
AS568-047	4.489	114.02	0.070	1.78	2.49	AS 568
AS568-048	4.739	120.37	0.070	1.78	2.49	AS 568
AS568-049	4.989	126.72	0.070	1.78	2.49	AS 568
AS568-050	5.239	133.07	0.070	1.78	2.49	AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-102	0.049	1.24	0.103	2.62	3.66	AS 568
AS568-103	0.081	2.06	0.103	2.62	3.66	AS 568
AS568-104	0.112	2.84	0.103	2.62	3.66	AS 568
AS568-105	0.143	3.63	0.103	2.62	3.66	AS 568
AS568-106	0.174	4.42	0.103	2.62	3.66	AS 568
AS568-107	0.206	5.23	0.103	2.62	3.66	AS 568
AS568-108	0.237	6.02	0.103	2.62	3.66	AS 568
AS568-109	0.299	7.59	0.103	2.62	3.66	AS 568
AS568-110	0.362	9.19	0.103	2.62	3.66	AS 568
AS568-111	0.424	10.77	0.103	2.62	3.66	AS 568
AS568-112	0.487	12.37	0.103	2.62	3.66	AS 568
AS568-113	0.549	13.94	0.103	2.62	3.66	AS 568
AS568-114	0.612	15.54	0.103	2.62	3.66	AS 568
AS568-115	0.674	17.12	0.103	2.62	3.66	AS 568
AS568-116	0.737	18.72	0.103	2.62	3.66	AS 568
AS568-117	0.799	20.29	0.103	2.62	3.66	AS 568
AS568-118	0.862	21.89	0.103	2.62	3.66	AS 568
AS568-119	0.924	23.47	0.103	2.62	3.66	AS 568
AS568-120	0.987	25.07	0.103	2.62	3.66	AS 568
AS568-121	1.049	26.64	0.103	2.62	3.66	AS 568
AS568-122	1.112	28.24	0.103	2.62	3.66	AS 568
AS568-123	1.174	29.82	0.103	2.62	3.66	AS 568
AS568-124	1.237	31.42	0.103	2.62	3.66	AS 568
AS568-125	1.299	32.99	0.103	2.62	3.66	AS 568
AS568-126	1.362	34.59	0.103	2.62	3.66	AS 568
AS568-127	1.424	36.17	0.103	2.62	3.66	AS 568

Dash number	Inner diameter d1 (in)	Inner diameter d1 (mm)	Cross section CS (in)	Cross section CS (mm)	Groove width (mm)	Reference standard
AS568-128	1.487	37.77	0.103	2.62	3.66	AS 568
AS568-129	1.549	39.34	0.103	2.62	3.66	AS 568
AS568-130	1.612	40.94	0.103	2.62	3.66	AS 568
AS568-131	1.674	42.52	0.103	2.62	3.66	AS 568
AS568-132	1.737	44.12	0.103	2.62	3.66	AS 568
AS568-133	1.799	45.69	0.103	2.62	3.66	AS 568
AS568-134	1.862	47.29	0.103	2.62	3.66	AS 568
AS568-135	1.924	48.87	0.103	2.62	3.66	AS 568
AS568-136	1.987	50.47	0.103	2.62	3.66	AS 568
AS568-137	2.049	52.04	0.103	2.62	3.66	AS 568
AS568-138	2.112	53.64	0.103	2.62	3.66	AS 568
AS568-139	2.174	55.22	0.103	2.62	3.66	AS 568
AS568-140	2.237	56.82	0.103	2.62	3.66	AS 568

Video: AS 568 AS568 O-Rings (Inch Series) Specification



► Watch video: <https://www.youtube.com/watch?v=0TgSBqvME0k>

[How to Measure an O-Ring - O-Ring Slide Gauge](#)

Third-party video, selected automatically for this topic. It is not produced by Engineering Hardware and is not a specification source — use the tables on this page for dimensional data.

Inside the plant

Manufactured in our own plant

This part is cold-formed, threaded, heat-treated and finished in-house. The stages below are where its class and finish are actually decided.

1.



01

Cold heading

Wire rod is drawn to size and cold-formed into blanks. Forming rather than cutting keeps the grain flow continuous around the head, which is where a bolt is most likely to fail.

Head dimensions and under-head radius checked at set-up and per shift.



2.

02

Thread rolling

Threads are rolled between hardened dies rather than cut. Rolled threads are stronger in fatigue than cut threads and hold pitch and flank angle far more consistently across a batch.

Go / no-go ring gauges to ISO 965 tolerance class 6g.

3.



03

Heat treatment

Quench-and-temper brings carbon and alloy steel to the property class ordered — 8.8, 10.9 or 12.9 — with the furnace charge tracked so a finished lot can be traced back to it.

Core hardness and tensile tested per lot to ISO 898-1.

4.



04

Surface treatment

Zinc, zinc-nickel, hot-dip galvanizing, black oxide, phosphate and Dacromet, selected against the service environment rather than against the price list.

Coating thickness and neutral salt spray hours to ISO 9227.

Frequently Asked Questions

What does AS 568 specify for AS568 O-Rings (Inch Series)?

AS 568 specifies the dimensions and tolerances of as568 o-rings (inch series). Material and property class are governed by separate standards in the same family.

Does AS 568 specify the mechanical strength?

No. AS 568 controls the dimensional requirements for as568 o-rings (inch series). Mechanical performance is set by the standards specific to this part family — ISO 898-1 and ISO 898-2 apply to bolts, screws and nuts and do not cover this product.

Can I substitute AS 568 for the corresponding DIN standard on a drawing?

On modern drawings the ISO standard is the master reference; the older DIN equivalent is a cross-reference. For most dimensional purposes the parts are interchangeable, but check tolerance grades and the head height — these are the most common points of

divergence.

Which edition of AS 568 does this table follow?

The table reproduces the dimensions we supply as568 o-rings (inch series) to. We do not publish an edition year against it, so where the edition is contractually significant, cite the edition you require on the enquiry and we will confirm it against the table before quoting.

How do I request a quotation?

Use the technical drawing on this page to pick the exact configuration, then submit it with the quote form. We respond within one business day.

Related Pages

[View the full AS568 O-Rings \(Inch Series\) page](#)